

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, 18075
T. 22 S., R. 7 W., Willamette Meridian, Oregon

CHAINS	
	<p style="text-align: center;">A fir, 32 ins. diam., bears N. 78 1/2° W., 583 lks. dist., mkd. E 1/16 S35 BT.</p> <p>From this point, the standard cor. of secs. 1 and 2, T. 23 S., R. 7 W., bears N. 88° 47' E., 13.87 chs. dist., hereinbefore described.</p>
	<p>From the 1/4 sec. cor. of secs. 34 and 35.</p> <p>N. 0° 09' W., bet. secs. 34 and 35.</p>
3.00	<p>Creek, 5 lks. wide, course S. 80° W.; asc. over SW. slope.</p>
28.90	<p>Dirt road, 15 lks. wide, bears N. 70° W. and S. 70° E.</p>
29.10	<p>Ridge, bears N. 70° W. and S. 70° W.; desc. over NE. slope.</p>
35.28	<p>From this point, the original closing cor. of secs. 26 and 35, bears East, 0.055 chs. dist., perpetuated and recorded by Wilford N. Haines, Registered Land Surveyor, No. 239, in 1957, mkd. X CC on bedrock, from which the remaining original tree:</p> <p style="padding-left: 40px;">A fir, 27 ins. diam., bears S. 35° E., 37 lks. dist., with healed double blaze.</p> <p>and a bearing tree mkd. by Haines <i>FO OK 10/95 BY HOFFINE M119-78</i></p> <p style="padding-left: 40px;">A fir, 37 ins. diam., bears N. 30° W., 45 lks. dist., with scribe marks T22S R7W BT visible on bark blaze.</p> <p>Descend over NE. slope.</p>
35.90	<p>Spur, slopes NE.; desc. over NW. slope.</p>
39.13	<p>The cor. of secs. 27 and 34 only, reestablished and recorded by Wilford N. Haines, Registered Land Surveyor, No. 239, in 1957, and is accepted as the corner, monumented with a 1 in. "T" shaped iron rod, firmly set, projecting 15 ins. above ground, with a washer, 1 in. diam., mkd.</p> <p style="text-align: center;"> WILFORD N HAINES 239 SURVEY POINT DRAIN OREGON </p> <p style="text-align: right;"><i>FO OK 10/95 BY HOFFINE M119-78</i></p> <p>from which the remains of bearing trees mkd. by Haines</p> <p style="padding-left: 40px;">A fir, 26 ins. diam., bears S. 76 1/2° W., 45 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears N. 53 1/4° W., 40 lks. dist., with healed blaze.</p> <p>At the corner point</p> <p>Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over iron rod, with aluminum cap mkd.</p>