

County Surveyor's Record, Douglas County, Oregon

18078 Dependent Resurvey, Portion of Subdivisional Lines
T. 22 S., R. 7 W., Willamette Meridian, Oregon

CHAINS	T 22 S R 7 W S 27/S 26 S 34/ 1984
	Land, mountainous. Soil, rocky clay. Timber, fir, hemlock, oak, madrone, cedar, yew, maple, chinquapin, and alder; undergrowth, Oregon grape, salal, hazel, arrowwood, vine maple, blackberry, ferns, poison oak, and young timber.
	N. 0° 13' W., bet. secs. 26 and 27 Descend over NW. slope, through heavy timber and dense undergrowth.
13.85	Hancock Creek, 8 lks. wide, course N. 60° W.; asc. over broken SW. slope.
15.47	From this point, a point established and recorded by Wilford N. Haines, Registered Land Surveyor, No. 239, in 1957, bears East, 0.04 chs. dist., monumented with a 1 in. "T" shaped iron rod, firmly set, projecting 12 ins. above ground, from which the remains of bearing trees mkd. by Haines: <p style="margin-left: 40px;">A sawed fir stump, 32 ins. diam., bears N. 85° E., 16 1/2 lks. dist., with healed blaze.</p> <p style="margin-left: 40px;">A fir snag, 33 ins. diam., bears N. 45° W., 32 lks. dist., with healed blaze.</p> Ascend over broken SW. slope.
36.00	Spur, slopes S. 85° W.; asc. over broken SW. slope.
36.58	The 1/4 sec. cor. of secs. 26 and 27, reestablished and recorded by Wilford N. Haines, Registered Land Surveyor No. 239, in 1957, and is accepted as the corner, monu- mented with a 1 in. "T" shaped iron rod, firmly set, projecting 5 ins. above ground, with a washer, 1 in. diam., mkd. <p style="text-align: center; margin: 10px 0;"> WILFORD N HAINES 239 SURVEY POINT DRAIN OREGON </p> from which the remains of bearing trees mkd. by Haines <p style="margin-left: 40px;">A fir, 25 ins. diam., bears S. 72 3/4 E., 33 lks. dist., with healed blaze.</p> <p style="margin-left: 40px;">A fir, 53 ins. diam., N. 73° W., 156 lks. dist., with scribe marks 1/4 S27 BT visible on bark blaze.</p> At the corner point <p style="margin-left: 40px;">Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over iron rod, with brass cap mkd.</p>