

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 23,
18082 T 22 S., R. 7 W., Willamette Meridian, Oregon

CHAINS	
	<p>and a bearing tree mkd. by S. W. Cole, Deputy County Surveyor, in 1913</p> <p style="padding-left: 40px;">A black oak, 21 ins. diam., bears S. 38 1/2° E., 150 lks. dist., no marks visible. (Record, S. 41 3/4° E.)</p> <p>and a bearing tree mkd. by Jelley and Beck</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears S. 43° E., 8 lks. dist., with healed blaze.</p>
	<p>From the 1/4 sec. cor. of secs. 23 and 24, perpetuated and recorded by Wilford N. Haines, Registered Land Surveyor, No. 239, in 1957, further perpetuated and recorded by Milo E. Godfrey, Deputy County Surveyor, in 1962, monumented with a 3 in. "T" shaped iron rod, firmly set, projecting 12 ins. above ground, with brass disc mkd.</p> <p style="text-align: center;">WILFORD N HAINES 239 SURVEY POINT DRAIN OREGON</p> <p>from which the remaining original bearing tree</p> <p style="padding-left: 40px;">A cedar, 16, ins. diam., bears S. 55° W., 6 lks. dist., with healed blaze.</p> <p>and a bearing tree mkd. by Godfrey</p> <p style="padding-left: 40px;">A fir, 7 ins. diam., bears N. 32° E., 27 lks. dist., with healed blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground directly, over iron rod, with brass cap mkd.</p>
	<p>T 22 S R 7 W 1/4 S 23/S 24 1984</p>
	<p>N. 88° 13' W., on the E. and W. center line of sec. 23.</p> <p>Ascend over NE. slope, through heavy timber and dense undergrowth.</p>
3.10	Spur, slopes N. 45° E.; desc. over NW. slope.
4.55	Ravine, drains N. 10° W.; asc. over NE. slope.
8.65	Ridge, bears N. 45° W. and S. 60° E.; desc. over broken NW. slope.
16.40	Spur, slopes S. 50° W.; desc. over broken NW. slope.
34.95	Creek, 15 lks. wide, course N. 30° E.; asc. over E. slope.
37.49	The center 1/4 sec. cor. of sec. 23.
	Ascend over E. slope.

*Ed. 3/90
CS 63/104*