

# County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 23,  
T 22 S., R. 7 W., Willamette Meridian, Oregon 18085

CHAINS	
	<p>from which bearing trees mkd. by Jelley and Beck</p> <p>A hemlock, 22 ins. diam., bears S. 73° E., 47 lks. dist., with healed blaze. (Record, 36 lks.)</p> <p>A cedar 25 ins. diam., bears S. 61° W., 62 lks. dist., with scribe marks S22 visible on partially healed blaze.</p>
	<p>Subdivision of Section 35, T 22. S., R. 7 W., Willamette Meridian, Oregon</p>
	<p>From the 1/4 sec. cor. of sec. 35 only, on the S. bdy. of the Tp.</p> <p>North, on the N. and S. center line of sec. 35, marking and blazing the true line.</p> <p>Ascend over SW. slope, through heavy timber and dense undergrowth.</p>
3.25	Spur, slopes N. 80° W.; desc. over NW. slope.
7.15	Creek 2 lks. wide, course W.; asc. over SW. slope.
12.65	Spur, slopes W.; desc. over broken NW. slope.
18.90	Creek, 2 lks. wide, course W.; asc. over SW. slope.
20.05	Point for the center S 1/16 sec. cor. of sec. 35.
	<p>Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="margin-left: 40px;">C S 1/16/S 35 C 1984</p>
	<p>from which</p> <p style="margin-left: 40px;">A fir, 4 ins. diam., bears S. 82 1/2° E., 20 lks. dist., mkd. X BT</p> <p style="margin-left: 40px;">A fir, 8 ins. diam., bears N. 41° W., 58 lks. dist., mkd. CS 1/16 S35 BT.</p> <p>Continue ascent over SW. slope.</p>
39.15	Creek, 1 lk. wide, course S. 15° W., asc. over SE. slope.
40.10	<p>The center 1/4 sec. cor. of sec. 35, established and recorded by Wilford N. Haines, Registered Land Surveyor No. 239, in 1957, and is accepted as the corner, monumented with a 1 in. "T" shaped iron rod, firmly set, projecting 4 ins. above ground, with a washer, 1 in. diam., mkd.</p> <p style="text-align: center;">WILFORD N HAINES 239 SURVEY POINT DRAIN OREGON</p> <p>From which bearing trees mkd. by Haines</p>