

# County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 35,  
T 22 S., R. 7 W., Willamette, Meridian, Oregon

18087

CHAINS	
	<p>N. 89° 00' W., on the E. and W. center line of sec. 35.</p> <p>Ascend over NE. slope, through heavy timber and dense undergrowth.</p>
18.15	Creek, 1 lk. wide, course N. 55° E.; asc. over SE. slope.
19.84	<p>The center E 1/16 sec. cor. of sec. 35, established and recorded by Wilford N. Haines, Registered Land Surveyor, No. 239, in 1957, and is accepted as the corner, monumented with a 1 in. "T" shaped iron rod, firmly set, projecting 4 ins. above ground, with a washer, 1 in. diam., mkd.</p> <p style="text-align: center;">WILFORD N HAINES 239 SURVEY POINT DRAIN OREGON</p> <p>from which bearing trees mkd. by Haines</p> <p style="margin-left: 40px;">A fir, 28 ins. diam., bears N. 35° E., 51 lks. dist., with scribe marks E C 1/16 S35 BT visible on bark blaze.</p> <p style="margin-left: 40px;">A cedar, 15 ins. diam., bears S. 41 3/4° E., 26 lks. dist., with healed blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over iron rod, with brass cap mkd.</p> <p style="text-align: center;">C E 1/16 C S 35 1984</p> <hr style="width: 20%; margin: 10px auto;"/>
	<p>N. 88° 59' W., beginning new measurement.</p> <p>Ascend over SE. slope.</p>
0.05	Ravine, drains. S. 80° E.; asc. over NE. slope.
9.40	Ridge, bears N. 30° W. and S. 30° E.; desc. over broken SW. slope, also dirt road, 15 lks. wide, bears N. 30° W. and S. 30° E.
26.10	Creek, 1 lk. wide, course S. 20° W.; asc. over broken SE. slope.
26.57	The center 1/4 sec. cor. of sec. 35.
	<p>N. 88° 57' W., beginning new measurement.</p> <p>Ascend over broken SE. slope.</p>
19.25	Spur, slopes S. 15° W.; desc. over NW. slope.