

# County Surveyor's Record, Douglas County, Oregon

18088 Subdivision of Section 35,  
T 22 S., R 7 W.. Willamette Meridian, Oregon

CHAINS  
19.86

The center W 1/16 sec. cor. of sec. 35, established and recorded by Wilford N. Haines, Registered Land Surveyor, No. 239, in 1957, and is accepted as the corner, monumented with a 1 in. "T" shaped iron rod, firmly set, projecting 6 ins. above ground, with a washer, 1 in. diam., mkd.

WILFORD N HAINES  
239  
SURVEY POINT  
DRAIN OREGON

from which the remains of bearing trees mkd. by Haines

A sawed fir stump, 44 ins. diam., bears N. 17° E., 14 lks. dist., no marks visible.

A sawed fir stump, 19 ins. diam., bears N. 13° W., 12 lks. dist., with scribe marks BT visible on bark blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over iron rod, with brass cap mkd.

C W 1/16 C  
S 35  
1984

from which new bearing trees

A fir, 41 ins. diam., bears S. 73° E., 94 lks. dist., mkd. CW 1/16 S35 BT.

A fir, 8 ins. diam., bears S. 18 1/2° E., 49 lks. dist., mkd. CW 1/16 S35 BT.

N. 88° 55' W., beginning new measurement.

Descend over NW. slope.

3.20 Dirt road, 15 lks. wide, bears N. 10° W. and S. 10° E.

19.86 The 1/4 sec. cor. of secs. 34 and 35.

From the E 1/16 sec. cor. of sec. 35 only, on the S. bdy. of the Tp.

N. 0° 05' E., on the N. and S. center line of the SE 1/4 of sec 35.

Ascend over SW. slope, through scattering timber and moderate undergrowth.

10.60 Dirt road, 15 lks. wide, bears N. 55° W. and S. 55° E.

12.60 Ridge, bears NW. and SE.; desc. over NE. slope.

19.47 Point for the SE 1/16 sec. cor. of sec. 35, at intersection with the E. and W. center line of the SE 1/4.