

# County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 35,  
T 22 S., R 7 W., Willamette Meridian, Oregon

18089

CHAINS	
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SE 1/6 S 35 1984</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears N. 23° E., 31 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A fir, 13 ins. diam., bears N. 19° W., 15 lks. dist., mkd. SE 1/16 S35 BT.</p> <p>From this point, a point established and recorded by Wilford N. Haines, Registered Land Surveyor, No. 239, in 1957, bears N 89° 31' E., 0.47 chs. dist., monumented with a 1 in "T" shaped iron rod, firmly set, projecting 3 ins. above ground, with a washer, 1 in. diam., mkd.</p> <p style="text-align: center;">WILFORD N HAINES 239 SURVEY POINT DRAIN OREGON</p> <p>from which bearing trees mkd. by Haines</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears N. 10° E., 46 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir, 33 ins. diam., bears S. 47 1/2° W., 31 lks. dist., with scribe marks 1/16 SE BT visible on partially healed blaze.</p> <p>Continue over NE. slope.</p>
38.10	Creek, 1 lk. wide, course N. 50° E.; asc. over SE. slope.
38.70	Spur, slopes N. 85° E.; desc. over NE. slope.
39.00	Ravine, drains S 80° E.; asc. over SE. slope.
39.18	The center E 1/16 sec. cor. of sec. 35.
	<p>From the S 1/16 sec. cor. of secs. 35 and 36</p> <p>N. 89° 44' W., on the E. and W. center line of the SE 1/4 of sec. 35.</p> <p>Descend over NW. slope, through heavy timber and dense undergrowth.</p>
4.55	Creek, 1 lk. wide, course N. 20° E.; asc. over NE. slope.
19.825	The SE 1/16 sec. cor. of sec. 35.
22.20	Ridge, bears N. 20° W. and S. 20° E.; desc. over broken SW. slope, also dirt road, 15 lks. wide, bears N. 20° W. and S. 20° E.
46.37	The center S 1/16 sec. cor. of sec. 35.
	<p>From the W 1/16 sec. cor. of sec. 35 only, on the S. bdy. of the Tp.</p>