

# County Surveyor's Record, Douglas County, Oregon

18093

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 23 S., R. 8 W., Willamette Meridian, Oregon

**CHAINS**

set, projecting 3 ins. above the ground, with brass cap mkd.

T 23 S	R 8 W
S 26	S 25
S 35	S 36
1964	

from which remains of the original bearing trees

A maple, 25 ins. diam., bears S. 72° W.,  
64 lks. dist., with healed blaze.

A root hole, bears N. 30° W., 22 lks. dist.

and bearing trees mkd. by Brooks and Peterson

A fir, 11 ins. diam., bears N. 74° E.,  
51 lks. dist., with healed blaze.

A fir, 8 ins. diam., bears S. 46° W.,  
91 lks. dist., with healed blaze.

A fir, 11 ins. diam., bears N. 84° W.,  
87 lks. dist., with healed blaze.

From this point, United States Coast and Geodetic Survey triangulation station "KELLOGG" bears N. 48° 53' E., 108.93 chs. dist., monumented with an iron pipe, 4 ins. diam., firmly set, projecting 4 ins. above the ground, with standard brass tablet mkd. KELLOGG 1953.

N. 89° 34' W., bet. secs. 26 and 35, marking and blazing the true line.

Ascend over broken NE. slope, through dense timber and undergrowth.

7.85 Gravelled road, 20 lks. wide, bears N. 28° W. and S. 28° E.

9.85 Spur, slopes SE.; desc. over broken SW. slope.

11.80 Gravelled road, 20 lks. wide, bears NW. and S., in curve.

19.985 Point for the E 1/16 sec. cor. of secs. 26 and 35.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

E 1/16	S 26
	S 35
1984	

from which

A fir, 6 ins. diam., bears N. 8½° E., 35½ lks. dist., mkd. E 1/16 S26 BT.

A fir, 15 ins. diam., bears S. 1° E., 21 lks. dist., mkd. E 1/16 S35 BT.