

# County Surveyor's Record, Douglas County, Oregon

18096

Subdivision of Section 35,  
T. 23 S., R. 8 W., Willamette, Meridian, Oregon

CHAINS	
28.20	Gravelled road, 20 lks. wide, bears N. 40° E. and S. 40° W.; also leave timber, edge bears same, enter logged area.
29.80	Gravelled road, 20 lks. wide, bears N. 10° E. and S. 40° E., in curve.
39.64	<p>Point for the center 1/4 sec. cor. of sec. 35, at intersection with the E. and W. center line of sec. 35.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 S R 8 W C ¼ S 35 1984</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears S. 73° W., 244 lks. dist., mkd. C ¼ S35 BT.</p> <p style="padding-left: 40px;">No other suitable trees available.</p> <p>Descend over broken N. slope.</p>
53.45	Gravelled road, 20 lks. wide, bears NE. and SW.; enter timber, edge bears same.
68.45	Waggoner Creek, 20 lks. wide, course S. 45° E.; asc. SW. slope.
69.50	Gravelled road, 20 lks. wide, bears NW. and SE.; leave timber, enter logged area, edge bears same.
79.53	The ¼ sec. cor. of secs. 26 and 35.
<p>From the ¼ sec. cor. of secs. 35 and 36, perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1956, subsequently recorded by Leslie D. Roberts, Registered Land Surveyor, No. 1039, in 1982, monumented with an iron post, 1½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 S R 8 W           ¼ S 35   S 36 1956</p> <p>from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A fir stump, 56 ins. diam., bears N. 52° E., 31 lks. dist., no marks visible.</p> <p>and the remains of bearing trees mkd. by Byron</p> <p style="padding-left: 40px;">A fir snag, 14 ins. diam., bears S. 50° E., 5½ lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir stump, 18 ins. diam., bears S. 78½° W., 37 lks. dist., with healed blaze.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A hemlock, 12 ins. diam., bears S. 43° W., 34 lks. dist., mkd. ¼ S35 BT.</p>	