

County Surveyor's Record, Douglas County, Oregon

18097

Subdivision of Section 35,
T. 23 S., R. 8 W., Willamette Meridian, Oregon

CHAINS


Corner is located at E. edge of timber, bears N. and S.
N. 89° 33' W., on the E. and W. center line of sec. 35.

Descend along broken N. slope, through moderate timber
and undergrowth.

9.20 Ravine, drains N. 20° E.; asc. over broken E. slope.

19.98 Point for the center E 1/16 sec. cor. of sec. 35.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.



from which

A fir, 8 ins. diam., bears S. 33½° W.,
17½ lks. dist., mkd. CE 1/16 S35 BT.

A fir, 6 ins. diam., bears N. 63° W.,
25½ lks. dist., mkd. X BT.

Corner is located on spur, slopes E.

Continue ascent over E. slope.

23.98 Spur, slopes N.; desc. over broken NW. slope.

26.35 Leave timber; enter logged area, edge bears Irregularly
NE. and SW.

37.35 Gravelled road, 20 lks. wide, bears N. 10° E. and
S. 10° W.


39.96 The center ¼ sec. cor. of sec. 35.

Continue descent over NW. slope.

44.60 Gravelled road, 20 lks. wide, bears N. 15° E. and
S. 15° W.

66.80 Enter timber, edge bears N. and S.

79.98 The ¼ sec. cor. of secs. 34 and 35, perpetuated and
recorded by Vernon R. Tracy, Deputy County Surveyor, in
1966, monumented with an iron post, 1½ ins. diam.,
firmly set, projecting 4 ins. above ground, with brass
cap mkd.



from which the remains of an original bearing tree

A fir snag, 48 ins. diam., bears N. 45° E.,
24 lks. dist., no marks visible on opened blaze.