

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 31 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

COUNTY SURVEYORS OFFICE

T 31 S
S 7 | S 8
S 18 | S 17
R 7 W
1975

from which the remains of original bearing trees

A sawed fir stump, 30 ins. diam., bears N. 13° E.,
26 lks. dist., no marks visible.

A decayed fir snag, size indeterminate, bears
S. 45° E., 18 lks. dist., with fragmentary scribe
marks visible on bark blaze.

A fir, 39 ins. diam., bears S. 80° W., 43 lks.
dist., remarked S18 CS BT on bark blaze.
(Record, 48 lks.)

A fir, 38 ins. diam., bears N. 44° W., 37 lks.
dist., with healed blaze and remarked S7 CS BT
on bark blaze.

and bearing trees mkd. by Goodwin.

A Madrone, 8 ins. diam., bears N. 62° E., 28 lks.
dist., with scribe marks T31S R7W S8 BT visible
on open blaze.

An oak, 8 ins. diam., bears S. 68° E., 33 lks.
dist., with scribe marks T31S R7W S17 BT visible
on open double blaze.

N. 0° 10' E., bet. secs. 7 and 8, marking and blazing
the true line.

Descend over broken NE. slope, through heavy timber and
dense undergrowth.

32.80 Dads Creek, 10 lks. wide, course S. 65° E.; asc. over
SE slope.

40.53 Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 8, at propor-
tionate distance; there is no remaining evidence of the
original corner.

Set an aluminum post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 23
ins. in the ground, with aluminum cap mkd.

T 31 S R 7 W
 $\frac{1}{4}$
S 7 | S 8
1985

from which

A fir, 6 ins. diam., bears N. 41 $\frac{1}{2}$ ° E., 36 lks.
dist., mkd. $\frac{1}{4}$ S8 BT.

A fir, 5 ins. diam. bears N. 73 $\frac{1}{2}$ ° W., 16 $\frac{1}{2}$ lks.
dist., mkd. $\frac{1}{4}$ S7 BT.

Ascend over SE. slope.