

County Surveyor's Record, Douglas County, Oregon

18106

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 30 S., R. 8 W., Willamette Meridian, Oregon

CHAINS	
	<p>Beginning at the $\frac{1}{4}$ sec. cor. of secs. 25 and 36, perpetuated and recorded by Vernon R. Tracy, Deputy County Surveyor, in 1965, monumented with an iron post, $1\frac{1}{2}$ inches diam., firmly set, projecting 6 ins. above ground, with original stone alongside, firmly set, projecting 4 ins. above ground, with marks $\frac{1}{4}$ visible on N. face, with brass cap mkd.</p>
	<p>COUNTY SURVEYORS OFFICE T 30 S $\frac{1}{4}$ $\frac{S\ 25}{S\ 36}$ R 8 W 1965</p>
	<p>from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A sawed fir stump, 31 ins. diam., bears S. 33° W., 80 lks. dist., with fragmentary scribe marks visible on opened blaze.</p> <p>and the remains of bearing trees mkd. by Tracy</p> <p style="padding-left: 40px;">A sawed fir stump, 14 ins. diam., bears S. 7° W., 13 lks. dist., with healed double blaze.</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears N. 34° W., 14 lks. dist., with healed double blaze.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears S. 46° E., 34 lks. dist., mkd. $\frac{1}{4}$ S36 BT.</p> <p>S. 88° 30' W., bet. secs. 25 and 36, marking and blazing the true line.</p> <p>Ascend over SE. slope, through heavy timber and dense undergrowth.</p>
0.65	<p>Spur, slopes S. 30° E.; desc. over broken SW. slope.</p>
10.915	<p>Point for the W 1/16 sec. cor. of secs. 25 and 36.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">W 1/16 $\frac{S\ 25}{S\ 36}$ 1985</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears S. 21° E., 33 lks. dist., mkd. W 1/16 S36 BT.</p> <p style="padding-left: 40px;">A fir, 5 ins. diam., bears N. 60° W., 21 lks. dist., mkd. W 1/16 S25 BT.</p> <p style="padding-left: 40px;">Deposit white "DEEP-1" magnetic marker at base of stainless steel post.</p>
25.85	<p>Dirt road, 15 lks. wide, bears N. 35° W. and S. 35° E.</p>
29.50	<p>Table Creek, 12 lks. wide, course S. 60° E.; asc. over broken NE. slope.</p>