

County Surveyor's Record, Douglas County, Oregon

18108

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 30 S., R. 8 W., Willamette Meridian, Oregon

CHAINS	
	<p>A fir snag, 39 ins. diam., bears S. 64° W., 18 lks., dist., with scribe marks $\frac{1}{4}$ S26 CS BT visible on bark blaze.</p> <p>and a bearing tree mkd. by Byron</p> <p>A fir, 10 ins. diam., bears S. 76$\frac{1}{2}$° E., 70 lks. dist., with healed double blaze.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2$\frac{1}{2}$ ins. diam., with magnetic, plastic breakaway base, 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 30 S R 8 W</p> <p style="margin-left: 100px;">$\frac{1}{4}$</p> <p style="margin-left: 80px;">S 26 S 25</p> <p style="margin-left: 100px;">1985</p> </div> <p>and a new bearing tree</p> <p>A fir, 28 ins. diam., bears N. 6° W., 30 lks. dist., mkd. $\frac{1}{4}$ S26 BT.</p> <p>Deposit steel fence post alongside iron post.</p> <p>The corner is located on a ridge, bears N. 85° E. and N. 85° W.</p> <p>From this point, United States Coast and Geodetic Survey triangulation station "LIVE OAK 1942" bears N. 73° 13' W., 72.54 chs. dist., set in concrete post, 10 ins. sq., firmly set flush with the ground, with top mkd. LIVE OAK 1942.</p> <p>N. 1° 17' E., bet. secs. 25 and 26.</p> <p>Descend over broken NE. slope, through heavy timber and dense undergrowth.</p>
0.85	Gravelled road, 20 lks. wide, bears N, 40° W. and N. 75° E., in curve.
18.60	Gravelled road, 25 lks. wide, bears N. 30° W. and S. 30° E.
19.325	<p>Point for the N 1/16 sec. cor. of secs. 25 and 26.</p> <p>Set a stainless steel post, 28 ins. long 2$\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>N 1/16</p> <p style="margin-left: 40px;">S 26 S 25</p> <p style="margin-left: 40px;">1985</p> </div> <p style="text-align: right; margin-right: 50px;">Fd. ok by T. Hostetter 11/2010 - C.S. File 65/69-62</p>
	<p>from which</p> <p>A fir, 10 ins. diam., bears S. 32° E., 53 lks. dist., mkd. N. 1/16 S25 BT.</p> <p>A fir, 6 ins. diam., bears N. 20° W., 96 lks. dist., mkd. N 1/16 S26 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p>