

County Surveyor's Record, Douglas County, Oregon

18110

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 30 S., R.8 W., Willamette Meridian, Oregon

CHAINS

A sawed fir stump, 27 ins. diam., bears N. 62½° W.,
85 lks. dist., with scribe marks BT visible on
partially healed blaze.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., with
magnetic, plastic breakaway base, 26 ins. in the ground,
with brass cap mkd.

T 30 S R 8 W
¼ $\frac{S\ 24}{S\ 25}$
1985

and new bearing trees

A fir, 16 ins. diam., bears N. 74½° E.,
21 lks. dist., mkd. ¼ S24 BT.

A grand fir, 9 ins. diam., bears S. 40½° W.,
130 lks. dist., mkd. ¼ S24 BT.

Deposit the iron pipe alongside the iron post.

S. 88° 09' W., bet. secs. 24 and 25.

Ascend over broken NE. slope, through heavy timber and
dense undergrowth.

7.10 Spur, slopes N.; desc. over broken NW. slope.

38.20 Ravine, drains N. 35° E.; asc. over NE. slope.

39.80 The cor. of secs. 23, 24, 25, and 26.

Land, mountainous.

Soil, rocky clay.

Timber, fir, cedar, hemlock, pine, madrone, alder, and
chinquapin; undergrowth, poison oak, manzanita,
huckleberry, arrowwood, hazel, ferns, and young timber.

From the cor. of secs. 3, 4, 9, and 10, perpetuated and
recorded by Vernon R. Tracy, Deputy County Surveyor, in
1965, monumented by the original corner tree, a fir
snag, 62 ins. diam., with scribe marks T30S R8W S3
visible on bark blaze on NE. face, from which new
bearing trees:

A hemlock, 6 ins. diam., bears N. 80° E.,
73 lks. dist., mkd. X BT.

A fir, 4 ins. diam., bears S. 42½° E.,
35 lks. dist., mkd. X BT.

A grand fir, 19 ins. diam., bears S. 21° W.,
76 lks. dist., mkd. T30S R8W S9 BT.

A grand fir, 9 ins. diam., bears N. 51½° W.,
44 lks. dist., mkd. T30S R8W S4 BT.

From this point, a witness corner established and
recorded by Vernon R. Tracy, Deputy County Surveyor, in
1965, bears South, 0.15 chs. dist., monumented with an
iron post, 1½ ins. diam., firmly set, projecting 6 ins.
above ground, with brass cap mkd.