

# County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 25,  
T 30 S., R. 8 W., Willamette Meridian, Oregon

18113

CHAINS	
10.70	Spur, slopes S. 75° W.; desc. over NW. slope.
39.61	<p>Point for the center 1/4 sec. cor. of sec. 25, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 30 S R 8 W C ¼ S 25 1985</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 4 ins. diam., bears N. 60½° E., 26 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A fir, 5 ins. diam., bears S. 39° E., 12 lks. dist., mkd. C¼ S25 BT.</p> <p style="padding-left: 40px;">Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Descend over broken NW. slope.</p>
45.90	Creek, 8 lks. wide, course S. 55° W.; asc. over broken SW. slope.
47.85	Dirt road, 25 lks. wide, bears N. 55° E. and S. 65° W.
59.15	<p>Point for the center N 1/16 sec. cor. of sec. 25.</p> <p>Set a stainless steel post, 28 ins. long 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">C N 1/16   S 25 C 1985</p> <p style="text-align: right;">Fd BC and 2 BTs by D. Edwards 4/2017 C.S. file 65/96-6 Set 6 ft. steel post 2 ft. north on line</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 4 ins. diam., bears S. 74° E., 13½ lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A grand fir, 7 ins. diam., bears S. 22° W., 34½ lks. dist., mkd. CN 1/16 S25 BT.</p> <p style="padding-left: 40px;">Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Ascend over SW. slope.</p>
70.90	Dirt road, 25 lks. wide, bears N. 80° W. and S. 80° E.
71.25	Ridge, bears N. 85° W. and S. 75° E.; desc. over broken NE. slope.
78.69	The ¼ sec. cor. of secs. 24 and 25.
	<p>From the ¼ sec. cor. of secs. 25 and 30, on the E. bdy. of the Tp., perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1964, monumented with an iron post, 1½ ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.</p>