

County Surveyor's Record, Douglas County, Oregon

18114

Subdivision of Section 25,
T 30 S., R 8 W., Willamette Meridian, Oregon

CHAINS

COUNTY SURVEYORS OFFICE

T 30 S
R ½ R
8 S 25 | S 30 7
W W
 1964

from which the remains of the original bearing trees

A fir snag, size indeterminate, bears S. 72° E.,
22 lks. dist., no marks visible.

A fir, 36 ins. diam., bears N. 64° W., 22 lks.
dist., with healed blaze, rescribed by Byron,
with scribe marks CS visible on bark blaze.

and the remains of a bearing tree mkd. by Byron

A sawed fir stump, 18 ins. diam., bears S. 72° E.,
61 lks. dist., with healed blaze.

and a new bearing tree

A fir, 32 ins. diam., bears N. 74° E.,
98 lks. dist., mkd. ½ S30 BT.

S. 88° 50' W., on the E. and W. center line of sec. 25.

Ascend over SE. slope, through heavy timber and dense
undergrowth.

1.60 Junction of dirt and gravelled roads, 25 lks. wide,
bears S. 60° E., S. 60° W., and N. 30° W.

9.60 Spur, slopes N. 50° E., to saddle; desc. over broken NW.
slope.

39.48 The center ½ sec. cor. of sec. 25.

Descend over broken NW. slope.

44.80 Creek, 4 lks. wide, course NW; desc. over broken NW.
slope.

58.45 Creek, 10 lks. wide, course SW.; asc. over SE. slope.

59.56 Point for the center W 1/16 sec. cor. of sec. 25.

Set a stainless steel post, 28 ins. long, 2½ ins. diam.,
22 ins. in the ground, with brass cap mkd.

W 1/16
C S 25 C
 1985

from which

A fir, 16 ins. diam., bears N. 60° E., 142
lks. dist., mkd. CW 1/16 S25 BT.

A pine, 10 ins. diam., bears S. 50° E., 15½
lks. dist., mkd. CW 1/16 S25 BT.

Deposit a white "DEEP-1" magnetic marker at
base of stainless steel post.

Ascend over SE. slope.