

County Surveyor's Record, Douglas County, Oregon

18118

T. 24 S., R. 8 Sw., Willamette Meridian, Oregon

CHAINS

The geographic position of the $\frac{1}{4}$ section corner of sections 35 and 36, as determined from a tie to Douglas County Surveyors Office triangulation station U-14, is as follows:

Latitude 43° 26' 25.24" N. Longitude 123° 36' 12.22" W.

The mean magnetic declination is 20° E.

Dependent Resurvey of a Portion of the South Boundary,
T. 24 S., R. S W., Willamette Meridian, Oregon.

(Restoring the survey by William H. Byars, in 1878, the retracement by Addison R. and Samuel C. Flint, in 1881, the retracement by Morris Wygant, in 1911, and the resurvey by Harold D. Corbin, in 1959)

Beginning at the cor. of secs. 1, 2, 35, and 36, on the S. bdy. of the tp., perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1958, monumented with an iron post, 1½ ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 24 S	S 35	S 36 8	R
	S 2	S 1	W
T 25 S			
1958			

from which the remains of the original bearing trees

A root hole, bears. M. 40° E., 15lks. dist., with a fir, 25 ins. diam., lying alongside, with a decayed blaze.

A fir snag, 38 ins. diam., bears S. 5 ° W., 21 ½ lks. dist., with illegible bark scribing. (Record, 20 lks.)

and the remains of bearing trees mkd. by Byron

A red fir, 18 ins. diam., bears N. 65½° E., 81 lks. dist., with a healed blaze.

A cedar snag, 30 ins. dia., bears N. 38° w., 39½ lks. dist., with scribe marks T24S R8W S35 CS visible on a weathered blaze. (Record, 38 lks.)

and bearing trees mkd. by Bruce Rogers, Deputy County Surveyor, in 1965

A fir, 15 ins. diam., bears S. 77° E., 16lks. dist., with healed blaze.

A fir, 12 ins. diam., bears S. 35° W., 31 lks. dist., with healed blaze.

A fir, 13 ins, diam., bears N. 63° W., 34 lks. dist., with healed blaze.