

County Surveyor's Record, Douglas County, Oregon

18119 Dependent Resurvey of a Portion of the South Boundary,
T. 24 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

Corner is 30 lks. W. of a spur, slopes N. 30° W.,
N. 89° 45' W., bet. secs. 2 and 35.

Descend over a broken SW. slope, through heavy timber
and dense undergrowth.

- 7.90 East edge of marsh, bears N. and S.
- 10.90 West edge of marsh, bears N. and S.; asc. over broken
NE. slope.
- 19.60 Spur, slopes SE.; desc. over broken SW. slope.
- 21.10 Gravel road, 30 lks. wide, bears N. 50° W., and S. 50° E.
- 36.50 Bottom of descent, bears NW. and SE.; cross gentle S.
slope.
- 39.22 The 1/4 sec. cor. of secs. 2 and 35, perpetuated and
recorded by James W. Byron, Deputy County Surveyor, in
1958, monumented with an iron post, 1½ ins. diam.,
firmly set, projecting 15 ins. above ground, with brass
cap mkd.

COUNTY SURVEYORS OFFICE
T 24 S
1/4 S 35 R
S 2 8
T 25 S W
1958

from which the remains of the original bearing trees

A fir snag, 12 ins. diam., bears S. 45° E., 26 lks.
dist., no marks visible on an opened blaze.

A fir stump, 30 ins. diam., bears N. 8° W., 28 lks.
dist., with bark scribed marks 3 B visible.

and the remains of a bearing tree mkd. by Byron

A cedar stump, 25 ins. diam., bears S. 70° W., 58
lks. dist., with scribe marks BT visible on
partially healed blaze.

and a bearing tree mkd. by Bruce Rogers Deputy County
Surveyor, in 1965

A cedar, 13 ins. diam., bears N. 31° E., 81½ lks.
dist., with a healed blaze.

and a new bearing tree

A fir, 18 ins. diam., bears S. 12° W., 18 lks.
dist., mkd. 1/4 S2 BT.

The corner is on level swampy ground.

S. 89° 55' W., beginning new measurement.

cross gentle S. slope.

- 7.00 Dirt road, 15 lks. wide, bears N. 40° W. and S. 40° E.