

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the South Boundary, **18120**
T. 24 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

- 12.60 Same road, bears N. and S. 20° W.
- 14.60 Begin ascent over broken SE. slope.
- 27.70 Gravel road, 20 lks. wide, bears N. 20° E. and S. 20° W.
- 37.69 The cor. of secs. 2, 3, 34, and 35, perpetuated and recorded by Arthur R. Evans, Registered Mining Engineer No. 2741, in 1956, and further perpetuated and recorded by James W. Byron, deputy County Surveyor, in 1958, monumented with an iron post, 1½ ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 24 S
R S 34 | S 35
8 S 3 | S 2
W T 25 S
1958

from which the remains of bearing trees mkd. by Wygant,

A fir snag, 28 ins. diam., bears S. 6½° E., 56 lks. dist., with opened and burned blaze.
(Record, S. 5° E.)

A cedar, 45 ins. diam., bears S. 28° W., 25 lks. dist., with healed blaze.

and a bearing tree mkd. by Evans

A fir, 30 ins. diam., bears N. 34° W., 38 lks. dist., with healed blaze. (Record, N. 35° W., 36 lks.)

and bearing trees mkd by Byron

A fir, 18 ins. diam., bears N. 69½° E., 55 lks. dist., with healed blaze.

A fir, 12 ins. diam., bears S. 81½° E., 40 lks. dist., with healed blaze.

Dependent Resurvey of a Portion of
the Subdivisional Lines,
T. 24 S., R. 8 W., Willamette Meridian, Oregon

(Restoring the survey by Dennis Hathorn, in 1858,
the resurvey and survey by Henry L. Chandler, in 1894,
and the remonumentation by Harold D. Corbin, in 1959.)

From the cor. of secs. 1, 2, 35, and 36, on the S. bdy. of the Tp.

N. 0° 37' W., bet. secs. 35 and 36.

Cross W. slope, through heavy timber and dense undergrowth.

- 1.30 Begin descent over broken NE. slope.

- 3.40 Dirt road, 30 lks. wide, bears N. 60° W. and S. 60° E.