

County Surveyor's Record, Douglas County, Oregon

18121

Dependent Resurvey, Portion of Subdivisioinal Lines,
T. 24 S., R. 8 W., Willamette Meridian, Oregon

CHAINS	
4.20	Ravine, drains E.; asc. over SE. slope.
6.00	Spur, slopes E.; desc. over broken NE. slope.
11.80	Creek, 2 lks. wide, course N. 70° E.; asc. over broken SE. slope.
17.50	Top of ascent, cross E. slope.
21.80	Dirt road, 10 lks. wide, bears E. and W.; begin descent over broken N. slope.
27.00	Ravine, drains N. 20° W.; asc. over SW. slope.
30.10	Top of ascent, cross W. slope.
33.20	Begin descent over NW. slope.
38.90	Creek, 5 lks. wide, course N. 50° E.; asc. over SE. slope.
42.65	The 1/4 sec. cor. of secs. 35 and 36, monumented with a sandstone, 24 x 12 x 4 ins. firmly set 12 ins. in the ground, mkd. ?4 on the E. face. (Record, basalt stone, mkd. on W. face.)
	from thich the remains of bearing trees mkd. by Chandler
	A madrone, 28 ins. diam., bears N. 21° E., 102 lks. dist., no visible marks. (Record, laurel, 100 lks.)
	A root hole, bears N. 9° W., 55 lks. dist., with a down fir, 35 ins. diam., lying alongside, with healed blaze. (Record N. 7½° W., 60 lks.)
	At the corner point
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 24 S R 8 W ½ S 35 S 36 1986
	from which new bearing trees
	A fir, 16 ins. diam., bears N. 60° E., 18 lks. dist., mkd. ¼ S36 BT.
	A fir, 12 ins. diam., bears S. 35° W., 28 lks. dist., mkd. ¼ S35 BT.
	Deposit the sandstone alongside and a white "DEEP-1" magnetic marker at base of stainless steel post.
	From this corner, Douglas County Surveyors Office triangulation station U-14 at latitude 43° 25' 51.08" N. and longitude 123° 33' 52.23" W., bears S. 71° 29' E., 165.05 chs. dist., monumented with a brass tablet, 3 ins. diam., set in the sidewalk, near the middle of the downstream side of the Tye Access Bridge, mkd. DOUGLAS COUNTY SURVEYORS OFFICE U-14 1972.