

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines
T. 24 S., R. 8 W., Willamette Meridian, Oregon

18122

CHAINS											
	N. 3° 56' W., beginning new measurement.										
	Ascend over a SE. slope.										
1.20	Spur, slopes E.; desc. over NE. slope.										
7.40	Creek, 1 lk. wide, course N. 40° E.; continue to desc. over broken NE. slope.										
10.10	Rock bluff, edge bears N. 60° W. and S. 60° E.; desc. over bluff.										
11.40	Asphalt road, 30 lks. wide, at base of bluff, bears N. 50° W. and S. 50° E.										
12.50	Wolf Creek, 60 lks. wide, course SE.; asc. over gentle S. slope.										
25.90	Begin ascent over steep SW. slope.										
26.90	Dirt road, 15 lks. wide, bears E. and W.										
39.66	The cor. of secs. 25, 26, 35, 36, perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1958, monumented with an iron post, 1½ ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.										
	<p>COUNTY SURVEYORS OFFICE</p> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2" style="text-align: center;">T 24 S</td></tr> <tr><td style="text-align: center;">S 26</td><td style="text-align: center;">S 25</td></tr> <tr><td style="text-align: center;">S 35</td><td style="text-align: center;">S 36</td></tr> <tr><td colspan="2" style="text-align: center;">R 8 W</td></tr> <tr><td colspan="2" style="text-align: center;">1958</td></tr> </table>	T 24 S		S 26	S 25	S 35	S 36	R 8 W		1958	
T 24 S											
S 26	S 25										
S 35	S 36										
R 8 W											
1958											
	from which the remains of the original bearing trees										
	A fir, 38 ins. diam., bears N. 85° E., 53 lks. dist., with healed blaze. (Record, 52 lks.)										
	A fir, 35 ins. diam., bears S. 80° E., 42 lks. dist., no visible marks on an opened blaze.										
	A decayed fir stump, 60 ins. diam., bears N. 73° W., 38 lks. dist., no marks visible. (Record, 35 lks.)										
	and bearing trees mkd. by Byron										
	A cedar, 22 ins. diam., bears N. 75° E., 65 lks. dist., with illegible scribe marks on a partially healed blaze.										
	A fir, 20 ins. diam., bears S. 51° E., 28½ lks. dist., with healed blaze.										
	A fir, 13 ins. diam., bears West, 30 lks. dist., with healed blaze.										
	A hemlock, 22 ins. diam., bears N. 72° W., 41½ lks. dist., with healed blaze.										
	From the cor. of secs. 2, 3, 34, and 35, on the S. bdy. of the Tp.										
	N. 1° 27' W., bet. secs. 34 and 35.										