

# County Surveyor's Record, Douglas County, Oregon

T. 31 S., R. 4 W., Willamette Meridian, Oregon

18128

**CHAINS**

The geographic position of the 1/4 section corner of sections 4 and 5, as determined from a tie made to triangulation station "HYDE," established by the United States Geological Survey, in 1953, is as follows:

Latitude 42° 54' 24.53" N. Longitude 123° 11' 16.70" W.

The geographic position of the corner of sections 1, 6, 7, and 12, on the east boundary of the township, as determined from a tie to United States Geological Survey triangulation station "BLAND MTN 1953", is as follows:

Latitude 42° 53' 57.57" N. Longitude 123° 06' 37.82" W.

The mean magnetic declination is 18° 30' E.

Dependent Resurvey of a Portion of the South Boundary,  
T. 30 S., R. 3 W., Willamette Meridian, Oregon

(Restoring the survey by William M. Bushey, in 1893-94)

Beginning at the 1/4 sec. cor. of sec. 31 only, on the S. bdy. of T. 30 S., R. 3 W., perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1963, monumented with the original stone, firmly set, projecting 2 ins. above ground, mkd. 1/4 on N. face, further monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 30 S  
1/4 South R  
S 31 3  
T 31 S S  
1963

from which the original bearing trees

A fir, 16 ins. diam., bears N. 56 1/2° E., 14 1/2 lks. dist., with healed blaze.

A fir, 20 ins. diam., bears S. 57 3/4° W., 27 1/2 lks. dist., with healed blaze.

S. 89° 29' W., on the S. bdy. of sec. 31, marking and blazing the true line.

Descend over NW. slope, through heavy timber and dense undergrowth.

5.73 True point for the closing cor. of Tps. 31 S., Rs. 3 and 4 W., hereinafter described.

6.65 Poole Creek, 10 lks. wide, course N. 5° W.; asc. over broken SE. slope.

13.50 Spur, slopes S. 65° E.; desc. over SW. slope.

15.50 Creek, 2 lks. wide, course S. 65° E.; asc. over SE. slope.