

County Surveyor's Record, Douglas County, Oregon

18129 Dependent Resurvey of a Portion of the South Boundary
T. 30 S., R. 3 W., Willamette Meridian, Oregon

CHAINS

45.57

Point for the 1/4 sec. cor. of sec. 1 only, T. 31 S., R. 4 W., hereinafter described.

Ascend over SE. slope.

48.21

The cor. of Tps. 30 S., Rs. 3 and 4., perpetuated and recorded by John H. Markham, Jr., Registered Engineer No. 2880, in 1959, monumented with an iron rod, 1 in. diam., firmly set, projecting 15 ins. above ground, from which the remains of the original bearing trees:

A decayed madrone stump, size indeterminate, bears S. 30° W., 39 lks. dist., with fragmentary scribe marks visible on decayed blaze. (Record, S. 31° W., 40 lks.)

A madrone, 18 ins. diam., bears N. 16° W., 48 1/2 lks. dist., remarked by Markham, with scribe marks T31S S1 visible on bark blaze. (Record, 50 lks.)

and a bearing tree mkd. by Thiel

A fir, 40 ins. diam., bears S. 51° E., 45 lks. dist., with scribe marks T31S S1 visible on bark blaze.

and bearing trees mkd. by Markham

A fir, 47 ins. diam., bears N. 41° E., 25 1/2 lks. dist., with scribe marks T30S R 31 BT visible on bark blaze.

A madrone, 12 ins. diam., bears N. 80° E., 67 1/2 lks. dist., with healed blaze.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, directly over iron rod, with brass cap mkd.

T 30 S	
R 4 W	R 3 W
S 36	S 31
S 1	
T 31 S R 4 W	
1985	

Deposit white "DEEP-1" magnetic marker at base of stainless steel post.

Land, mountainous.

Soil, rocky clay.

Timber, fir, hemlock, cedar, yew, pine, alder, maple, chinquapin, madrone, willow, and cherry; undergrowth, salal, Oregon grape, arrowwood, hazel, blackberry, huckleberry, vine maple, rhododendron, manzanita; and young timber.

Dependent Resurvey of a portion of the South Boundary,
T. 30 S., R. 4 W., Willamette Meridian, Oregon