

County Surveyor's Record, Douglas County, Oregon

18130

Dependent Resurvey of a Portion of the South Boundary,
T. 30 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
	<p>(Restoring the survey by Nathaniel Ford, in 1854, the resurvey by William Thiel, in 1889, and the retracement and resurvey by William M. Bushey, in 1893-4)</p> <hr style="width: 20%; margin: auto;"/>
	<p>From the cor. of Tps. 30 S., Rs. 3 and 4 W.</p> <p>S. 89° 38' W., on the S. bdy. of sec. 36.</p> <p>Ascend over broken SE. slope, through heavy timber and dense undergrowth.</p>
10.05	Dirt road, 15 lks. wide, bears N. 25° E. and S. 10° W.
21.25	Ridge, bears N. and S.; desc. over NW. slope.
23.00	Dirt road, 15 lks. wide, bears N. 10° E. and S. 10° W.
31.905	<p>The cor. of secs. 35 and 36, perpetuated and recorded by John H. Markham, Jr., Registered Engineer No. 2880, in 1960, monumented with an iron pipe, 1 in. diam., firmly set, projecting 12 ins. above ground, from which the remains of the original bearing trees:</p> <p style="margin-left: 40px;">A fir, 27 ins. diam., bears S. 31° W., 35 lks. dist., with healed blaze.</p> <p>and bearing trees mkd. by Markham</p> <p style="margin-left: 40px;">A madrone, 10 ins. diam., bears N. 74½° E., 30 lks. dist., with scribe marks T30S R4W S36 BT. visible on bark blaze.</p> <p style="margin-left: 40px;">A fir, 17 ins. diam., bears S 81 3/4° W., 7½ lks. dist., with healed blaze.</p> <p style="margin-left: 40px;">A fir, 17 ins. diam., bears N. 59½°W., 12 lks. dist., with healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 30 S R 4 W</p> <p style="margin-left: 40px;">S 35 S 36</p> <p style="margin-left: 80px;">S 1</p> <p>T31 S R 4 W</p> <p style="margin-left: 80px;">1985</p> </div> <p style="margin-left: 40px;">Deposit iron pipe alongside and white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Land, mountainous. Soil, rocky clay. Timber, fir cedar, madrone, pine, yew, hemlock, willow, alder, chinquapin, and oak; undergrowth, ferns, salal, hazel, Oregon grape, arrowwood, blackberry, huckleberry, rhododendron, manzanita, poison oak, and young timber.</p>
	<p>S 89° 31' W., on the S. bdy. of sec. 35.</p> <p>Descend over broken SW. slope, through heavy timber and dense undergrowth.</p>