

County Surveyor's Record, Douglas County, Oregon

18131 Dependent Resurvey of a Portion of the South Boundary,
T. 30 S., R. 4 W., Willamette Meridian., Oregon

<p>CHAINS 5.295</p> <p>17.30</p> <p>38.24</p>	<p>True point for the closing cor. of secs. 1 and 2, T. 31 S., R. 4 W., hereinafter described.</p> <p>Creek, 5 lks. wide, course N. 60° W.; asc. over broken NE. slope.</p> <p>The cor. established as the ¼ sec. cor. of secs. 2 and 35, by William Thiel, in 1889, and changed to an angle point by William M. Bushey, in 1893-94, determined from the remains of the original bearing trees:</p> <p style="padding-left: 40px;">A fir root crown, size indeterminate, bears S. 22° W., 18 lks. dist., no marks visible.</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears N. 2° W., 18 lks. dist., with mark / visible on opened blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>AP</p> <p>T 30 S R 4 W</p> <p style="margin-left: 40px;">S 35</p> <p style="margin-left: 40px;">S 2</p> <p>T 31 S</p> <p>1985</p> </div> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears S. 32½° W., 23 lks. dist., mkd. AP S2 BT.</p> <p style="padding-left: 40px;">A fir, 19 ins. diam., bears N. 59° W., 35 lks. dist., mkd. AP S35 BT.</p> <p>The corner is located on a steep NE. slope, 50 lks. E. of a spur, slopes N.</p> <p>Land, mountainous. Soil, rocky clay. Timber, fir, cedar, hemlock, yew, pine, oak, madrone, alder, chinquapin, and willow; undergrowth, poison oak, salal, hazel, Oregon grape, arrowwood, blackberry, wild rose, vine maple, huckleberry, manzanita, and young timber.</p>
	<p>From the cor. of secs. 4, 5, 32, and 33, on the S. bdy. of the Tp., determined at record bearing and distance from the remains of the original bearing trees:</p> <p style="padding-left: 40px;">A sawed fir stump, 66 ins. diam., bears S. 73° W., 28 lks. dist., axe marks visible on opened blaze.</p> <p style="padding-left: 40px;">A down, decayed madrone, size indeterminate, bears N 60½° W., 28 lks. dist., no marks remain.</p> <p>This point now becomes an angle point.</p> <p>At the corner point.</p> <p>Set a stainless steel post., 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>