

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the South Boundary, **18132**
T. 30 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

AP
T 30 S R 4 W
S 33
S 4
T 31 S
1985

from which new bearing trees

A fir, 13 ins. diam., bears S. 24 3/4° E., 31 lks. dist., mkd. AP S4 BT.

A fir, 10 ins. diam., bears N. 1° W., 39 lks. dist., mkd. AP S33 BT.

Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.

S. 89° 06' W., on the S. bdy. of the Tp.

Descend over steep W. slope, through moderate timber and dense undergrowth.

7.22

From this point, the original closing cor. of secs. 32 and 33, bears North, 0.112 chs. dist., perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1963, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. COUNTY SURVEYORS OFFICE T30S R4W CC S32 S33 T31S 1963, from which the remains of the original bearing trees:

A fir snag, 53 ins. diam., bears N. 25 1/2° E., 116 lks. dist., with healed blaze.

A fir 45 ins. diam., bears S. 33 3/4° E., 54 lks. dist., with healed blaze.

A decayed fir stump, size indeterminate, bears N. 25° W., 105 lks. dist., no marks remain.

and bearing trees mkd. by Byron.

A madrone, 10 ins. diam., bears N. 31 3/4° E., 49 lks. dist., mkd. CC T30S R4W S33 S BT.

A fir, 17 ins. diam., bears N. 33° W., 47 lks. dist., with healed blaze.

9.53

Point for the closing cor of secs. 4 and 5, T. 31 S., R. 4 W., at proportionate distance, hereinafter described.

12.55

Creek, 5 lks. wide, course N. 10° W.; asc. over NE. slope

14.05

Enter logged area, edge bears N. 25° W. and S. 10° E.; continue through thick undergrowth.

32.00

Spur, slopes N.; desc. over NW. slope.

33.75

Enter moderate timber edge bears S. 25° E. and N. 40° W.

39.09

Point for the 1/4 sec. cor. of secs. 5 and 32, determined by irregular boundary method; there is no remaining evidence of the original corner, this point now becomes an angle point.