

# County Surveyor's Record, Douglas County, Oregon

**18133** Dependent Resurvey of a Portion of the South Boundary,  
T. 30 S., R 4 W., Willamette Meridian, Oregon

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;">                     AP                      T 30 S R 4 W                      S 32  <hr style="width: 50px; margin: 0 auto;"/>                     S 5                      T 31 S                      1985                 </div> <p>from which</p> <p style="margin-left: 40px;">A fir, 31 ins. diam., bears N. 7¼° E., 72½ lks. dist., mkd. AP S32 BT.</p> <p style="margin-left: 40px;">A fir, 14 ins. diam., bears S. 80° E., 94½ lks. dist., mkd. AP S5 BT.</p> <p style="margin-left: 40px;">Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>The corner is located on steep NW. slope.</p> <hr style="width: 20%; margin: 20px auto;"/> <p style="margin-left: 40px;">S 89° 36' W., beginning new measurement</p> <p>Descend over NW. slope.</p>
1.80	Shoulder of gravelled road, 30 lks. wide, bears N. 40° E. and N. 40° W., in curve, also creek, 5 lks. wide, course N.; asc. steep E. slope.
10.45	Ridge, bears N. and S.; desc. NW. slope.
10.90	Enter logged area, edge bears N. and S.
15.25	Ravine, drains N. 50° E.; asc. broken NE. slope.
38.90	<p>The cor. of secs. 5, 6, 31, and 32, determined from the remains of the original bearing trees:</p> <p style="margin-left: 40px;">A sawed fir stump, 30 ins. diam., bears N. 45° E., 9 lks. dist., with scribe marks BT visible on opened blaze. (Record, N. 31° E.)</p> <p style="margin-left: 40px;">A sawed, decayed, fir stump, size indeterminate, bears S. 63½° W., 22 lks. dist., no marks remain.</p> <p style="margin-left: 40px;">A sawed fir stump, 50 ins. diam., bears N. 35° W., 56 lks. dist., with scribe marks T30S R4W BT visible. (Record, 62 lks.)</p> <p>This point now becomes an angle point.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;">                     AP                      T 30 S R 4 W                      S 32  <hr style="width: 50px; margin: 0 auto;"/>                     S 5                      T 31 S                      1985                 </div>

F/DOK  
 Ken Hoffline  
 A/gc 11/23-69