

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the South Boundary, **18134**  
T. 30 S., R 4 W., Willamette Meridian, Oregon

**CHAINS**

from which a new bearing tree

A fir, 14 ins. diam., bears N. 77 3/4° E., 74  
lks. dist., mkd. AP S32 BT.

No suitable tree available in sec. 5.

Deposit a white "DEEP-1" magnetic marker  
at base of stainless steel post.

Dependent Resurvey of a Portion of the East Boundary,  
T. 31 S., R. 5 W., Willamette Meridian, Oregon

(Restoring the survey by Butler Ives and George W. Hyde,  
in 1854, and the resurvey by Daniel L. Berry and  
Charles E. Akin, Jr., in 1972-73)

From the cor. of secs. 25 and 36 only, on the E. bdy. of  
T. 31 S., R. 5 W., monumented with an iron post, 1 1/4 ins.  
diam., firmly set, projecting 12 ins. above ground, with  
brass cap mkd.

COUNTY SURVEYORS OFFICE

T 31 S R 4 W

S 25		S31
S 36		

R 5 W

1966

from which the remains of the original bearing trees

A fir snag, 29 ins. diam., bears N. 50° E.,  
45 lks. dist., with healed blaze.

A fir, 40 ins. diam., bears S. 32° E.,  
41 lks. dist., with healed blaze.

A fir snag, 30 ins. diam., bears S. 36° W.,  
35 lks. dist., with healed blaze.

A fir stump, 30 ins. diam., bears N. 54° W., 31  
lks. dist., with scribe marks BT visible on  
opened blaze.

and the remains of bearing trees mkd. by John M. Powell,  
Deputy County Surveyor, in 1966

A cedar, 18 ins. diam., bears S. 51° E., 77  
lks. dist., with healed double blaze.

A fir snag, 8 ins. diam., bears N. 60° E., 75  
lks. dist., with healed double blaze.

and bearing trees mkd. by Berry and Akin

A fir, 8 ins. diam., bears S. 16° W., 10  
lks. dist., with healed double blaze.

A fir, 9 ins. diam., bears N. 6° W., 29 lks.  
dist., with healed double blaze. (Record,  
30 lks.)

N. 0° 09' E., on the E. bdy. of sec. 25, marking and  
blazing the true line.