

County Surveyor's Record, Douglas County, Oregon

18135 Independent Resurvey of a Portion of the East Boundary,
T. 31 S., R. 5 W., Willamette Meridian, Oregon

CHAINS																			
	Ascend over SW. slope, through heavy timber and dense undergrowth.																		
3.61	True point for the closing cor. of secs. 30 and 31, T. 31 S., R. 4 W., hereinafter described.																		
8.70	Dirt road, 15 lks. wide, bears N. 60° E. and S. 60° W.																		
9.85	Ridge, bears E. and W.; desc. over broken NE. slope.																		
23.62	Point for the S 1/16 sec. cor. of sec. 30 only, T. 31 S., R. 4 W., hereinafter described. Descend over broken NE. slope.																		
26.95	Ravine, drains N. 10° E.; desc. over broken NE. slope.																		
39.105	The 1/4 sec. cor. of sec. 25 only, monumented with an iron post 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 2px 5px;">1/4 S 25</td> <td style="border-left: 1px solid black; padding: 2px 5px;"> </td> <td></td> </tr> <tr> <td style="padding: 2px 5px;">T 31 S</td> <td style="border-left: 1px solid black; padding: 2px 5px;"> </td> <td></td> </tr> <tr> <td style="padding: 2px 5px;">R 5 W</td> <td style="border-left: 1px solid black; padding: 2px 5px;"> </td> <td></td> </tr> <tr> <td></td> <td></td> <td style="text-align: center; padding: 2px 5px;">1973</td> </tr> </table> </div> From which the bearing trees mkd. by Berry and Akin A fir, 25 ins. diam., bears S. 36° W., 63 lks. dist., with healed blaze. A fir, 20 ins. diam., bears N. 38° W., 31 lks. dist., with healed blaze. <hr style="width: 20%; margin: 10px auto;"/> N. 0° 30' E., beginning new measurement. Descend over broken NE. slope.	1/4 S 25			T 31 S			R 5 W					1973						
1/4 S 25																			
T 31 S																			
R 5 W																			
		1973																	
4.525	Point for the 1/4 sec. cor. of sec. 30 only, T. 31 S., R. 4W., hereinafter described. Descend over broken NE. slope.																		
38.67	The cor. of secs. 24 and 25, T. 31 S., R. 5 W., monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 16 ins. above ground, with brass cap mkd. <div style="margin-left: 20px;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="3" style="text-align: center; padding: 5px;">COUNTY SURVEYORS OFFICE</td> </tr> <tr> <td style="padding: 2px 5px;">T 31 S</td> <td style="padding: 2px 5px;">R 4 W</td> <td></td> </tr> <tr> <td style="padding: 2px 5px;">S 24</td> <td style="border-left: 1px solid black; padding: 2px 5px;"> </td> <td style="padding: 2px 5px;">S 30</td> </tr> <tr> <td style="padding: 2px 5px;">S 25</td> <td style="border-left: 1px solid black; padding: 2px 5px;"> </td> <td></td> </tr> <tr> <td style="padding: 2px 5px;">R 5 W</td> <td></td> <td></td> </tr> <tr> <td colspan="3" style="text-align: center; padding: 2px 5px;">1966</td> </tr> </table> </div> from which the remains of the original bearing trees A fir, 18 ins. diam., bears S. 10° E., 62 lks. dist., with healed blaze. A fir, 24 ins. diam., bears S. 68° W., 41 lks. dist., with healed blaze. and the remains of a bearing tree mkd. by Bushey A root hole, bears N. 60° W., 11 lks. dist.	COUNTY SURVEYORS OFFICE			T 31 S	R 4 W		S 24		S 30	S 25			R 5 W			1966		
COUNTY SURVEYORS OFFICE																			
T 31 S	R 4 W																		
S 24		S 30																	
S 25																			
R 5 W																			
1966																			

FD. OK 2/96
BY LANG M127-73