

County Surveyor's Record, Douglas County, Oregon

18139 Dependent Resurvey of a Portion of the East Boundary,
T. 31 S., R 4 W., Willamette Meridian, Oregon

CHAINS													
	<p>A fir, 14 ins. diam., bears S. $73\frac{1}{2}^\circ$ E., 54 lks. dist., with scribe marks X BT visible on partially healed blaze.</p> <p>and a new reference monument</p> <p>An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 45° W., 22.7 lks. dist., with brass cap mkd. RM LINE TREE S1 15 FT 1985, and an arrow pointing to the corner. Deposit white "DEEP 1" magnetic marker at base of stainless steel post.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>N. $0^\circ 02'$ W., beginning new measurement.</p> <p>Descend over broken NE. slope.</p>												
11.65	Creek, 5 lks. wide, course N. 40° W.; asc. over SW. slope.												
20.85	Spur, slopes N. 40° W.; desc. over NW. slope.												
34.45	Creek, 1 lk. wide, course, N. 60° W.; asc. over SW. slope.												
36.85	Spur, slopes W.; desc. over NW. slope.												
39.90	Intersect the S. bdy. of T. 30 S., R. 3 W.												
	<p>True point for the closing cor. of Tps. 31S., Rs. 3 and 4W.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2" style="border-top: 1px solid black; border-bottom: 1px solid black;">T 30 S R 3 W</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S 1</td><td style="padding: 0 5px;">S 6</td></tr> <tr><td colspan="2" style="text-align: center; padding: 0 5px;">C C</td></tr> <tr><td colspan="2" style="text-align: center; padding: 0 5px;">R 4 W R 3 W</td></tr> <tr><td colspan="2" style="text-align: center; padding: 0 5px;">T 31 S</td></tr> <tr><td colspan="2" style="text-align: center; padding: 0 5px;">1985</td></tr> </table> </div> <p>Deposit white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>From this point, the original closing cor. of Tps. 31 S., Rs. 3 and 4 W., bears N. $0^\circ 02'$ W., 0.027 chs. dist. perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1963, monumented with an iron post, $1\frac{1}{4}$ ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. COUNTY SURVEYORS OFFICE T30S R3W R4W CC S1 S6 T31S 1963, from which the original bearing trees:</p>	T 30 S R 3 W		S 1	S 6	C C		R 4 W R 3 W		T 31 S		1985	
T 30 S R 3 W													
S 1	S 6												
C C													
R 4 W R 3 W													
T 31 S													
1985													
	<p>A fir, 52 ins. diam., bears N. $34\frac{1}{2}^\circ$ E., $37\frac{1}{2}$ lks. dist., with healed blaze.</p> <p>A fir, 43 ins. diam., bears S. $55\frac{1}{2}^\circ$ E., $34\frac{1}{4}$ lks. dist., with healed blaze.</p> <p>A maple, 23 ins. diam., bears S. 67° W., $64\frac{1}{2}$ lks. dist., with scribe marks 31S R4W S1 visible on opened blaze. Rescribed by Byron.</p>												