

County Surveyor's Record, Douglas County, Oregon

18140

Dependent Resurvey of a Portion of the East Boundary,
T. 31 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

From this same point, the $\frac{1}{4}$ sec. cor. of sec. 31 only,
T. 30 S., R. 3 W., bears N. $89^{\circ} 29'$ E., 5.73 chs. dist.,
hereinbefore described.

Land, mountainous.

Soil, rocky clay.

Timber, fir, pine, hemlock, yew, cedar, alder,
chinquapin, maple, ash, dogwood, madrone and willow;
undergrowth, poison oak, arrowwood, vine maple, huckle-
berry, manzanita, rhododendron, ceanothus, blackberry,
hazel, salal, Oregon grape, ferns, and young timber.

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 31 S., R. 4 W., Willamette Meridian, Oregon

(Restoring the survey by William M. Bushey, in 1894)

From the cor. of secs. 1, 6, 7, and 12 on the E. bdy.
of the Tp.

N $89^{\circ} 25'$ W., bet. secs. 1 and 12, marking and blazing
the true line.

Descend over steep SW. slope, through heavy timber and
dense undergrowth.

19.66

The E $\frac{1}{16}$ sec. cor. of secs. 1 and 12, established and
recorded by John H. Markham, Jr., Registered Engineer
No. 2880, in 1960, and is accepted as the corner,
monumented with an iron rod $\frac{1}{2}$ in. diam., firmly set,
projecting 5 ins. above ground, from which bearing trees
mkd. by Markham:

A Maple, 8 ins. diam., bears N. 47° E., 17
lks. dist., with healed double blaze.

A fir, 38 ins. diam., bears N. 78° W., $18\frac{1}{2}$ lks.
dist., with scribe marks $\frac{1}{16}$ S1 BT visible
on bark blaze.

A fir, 36 ins. diam., bears N. 22° W., 42 lks.
dist., with scribe marks $\frac{1}{16}$ S1 BT visible
on bark blaze.

At the corner point

Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam.,
24 ins. in the ground, directly over the iron rod, with
brass cap mkd.

E $\frac{1}{16}$ $\frac{S 1}{S 12}$
 1985

from which a new bearing tree

A cedar, 4 ins. diam., bears S. 69° E., $12\frac{1}{2}$
lks. dist., mkd. X BT.

Deposit a white "DEEP-1" magnetic marker
at base of stainless steel post.