

# County Surveyor's Record, Douglas County, Oregon

**18141** Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 31 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
	<p>N. 89° 51' W., Beginning new measurement.</p> <p>Descend over SW. slope.</p>
4.05	<p>Poole Creek, 5 lks. wide, course NW.; asc. over broken NE. slope.</p>
19.735	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 1 and 12, perpetuated and recorded by John H. Markham, Jr., Registered Engineer No. 2880, in 1960, monumented with an iron rod, <math>\frac{1}{2}</math> in. diam., firmly set, projecting 4 ins. above ground, from which the original bearing trees:</p> <p style="margin-left: 40px;">A fir, 17 ins. diam., bears N. <math>4\frac{1}{2}^{\circ}</math> E., <math>19\frac{1}{2}</math> lks. dist. with healed blaze and rescribed by Markham, with scribe marks <math>\frac{1}{4}</math> S1 BT visible on bark blaze.</p> <p style="margin-left: 40px;">A fir, 33 ins. diam., bears S <math>26\frac{1}{2}^{\circ}</math> E., <math>14\frac{3}{4}</math> lks. dist., with healed blaze.</p> <p>and bearing trees mkd. by Markham</p> <p style="margin-left: 40px;">A fir, 20 ins. diam., bears N. <math>42\frac{3}{4}^{\circ}</math> E., <math>23\frac{1}{2}</math> lks. dist., with healed blaze.</p> <p style="margin-left: 40px;">A madrone, 21 ins. diam., bears N. <math>88^{\circ}</math> E., <math>29\frac{1}{2}</math> lks. dist., no marks visible.</p> <p style="margin-left: 40px;">A fir, 17 ins. diam., bears S. <math>74^{\circ}</math> W., 21 lks. dist., with healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, directly over the iron rod, with brass cap mkd.</p> <div style="text-align: center; margin: 20px 0;"> <p>T 31 S R 4 W</p> <p><math>\frac{1}{4}</math> <math>\frac{S 1}{S 12}</math></p> <p>1985</p> </div>
	<p>N. 88° 23' W., beginning new measurement.</p> <p>Ascend over broken NE. slope.</p>
2.45	<p>Spur, slopes N. <math>50^{\circ}</math> E.; asc. over broken NE. slope.</p>
18.30	<p>Spur, slopes N. <math>50^{\circ}</math> E.; asc. over broken NE. slope.</p>
20.07	<p>The W <math>\frac{1}{16}</math> sec. cor. of secs. 1 and 12, established and recorded by John H. Markham, Jr., Registered Engineer No. 2880 in 1960, and is accepted as the corner, monumented with an iron rod, <math>\frac{1}{2}</math> in. diam., firmly set projecting 6 ins. above ground, from which the bearing trees mkd. Markham:</p> <p style="margin-left: 40px;">A fir, 36 ins. diam., bears S. <math>48^{\circ}</math> E., <math>2\frac{1}{2}</math> lks. dist., with scribe marks <math>\frac{1}{16}</math> S BT visible on double bark blaze.</p> <p style="margin-left: 40px;">A fir, 47 ins. diam., bears N. <math>87^{\circ}</math> W., 31 lks. dist., with scribe marks <math>\frac{1}{16}</math> S12 BT visible on double bark blaze.</p>