

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 31 S., R. 4 W., Willamette Meridian, Oregon 18142

CHAINS	
	<p>A fir, 32 ins. diam., bears N. 69° W., 38 lks. dist., with scribe marks 1/16 S1 BT visible on double bark blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{r} \text{W } 1/16 \\ \hline \text{S } 1 \\ \hline \text{S } 12 \\ 1985 \end{array}$ </div> <p>Deposit iron rod alongside, and white "DEEP-1" magnetic marker at base of stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89° 07' W., beginning new measurement.</p> <p>Ascend over broken NE. slope.</p>
11.50	Ridge, bears N. 30° W. and S. 30° E.; desc. over SW. slope.
12.55	Dirt road, 20 lks. wide bears N. 30° W. and S. 30° E.
19.50	Head of ravine, drains S. 30° W.; asc. over SE. slope.
20.05	<p>The cor. of secs. 1, 2, 11, and 12, perpetuated and recorded by John H. Markham, Jr., Registered Engineer No. 2880, in 1960, monumented with the original stone, 10 x 6 x 6 ins., loosely set, projecting 6 ins. above ground, with 5 notches on the S. and 1 notch on the E. edges, (alongside of which is a flanged axle, 1¼ ins. diam., firmly set, projecting 4 ins. above ground,) from which the remains of the original bearing trees:</p> <p style="margin-left: 40px;">A fir, 34 ins. diam., N. 29° E., 60½ lks. dist., with healed blaze.</p> <p style="margin-left: 40px;">A madrone root crown, bears S. 84½° E., 19 lks. dist., no marks visible.</p> <p style="margin-left: 40px;">A madrone root crown, bears S. 20¼° W., 9½ lks. dist., no marks visible.</p> <p style="margin-left: 40px;">A madrone root crown, bears N. 61½° W., 49½ lks. dist., no marks visible.</p> <p>and bearing trees mkd. by Markham</p> <p style="margin-left: 40px;">A madrone, 8 ins. diam., bears S. 12½° W., 10½ lks. dist., with fragmentary scribe marks visible on bark blaze.</p> <p style="margin-left: 40px;">A madrone, 8 ins. diam., bears N. 80° W., 25 lks. dist., with scribe marks BT visible on bark blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>