

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 31 S., R. 4W., Willamette Meridian, Oregon 18141

CHAINS								
	N. 0° 35' E., beginning new measurement.							
	Descend over NE. slope.							
0.65	Creek, 1 lk. wide, course S. 75° E.; asc. over broken SE. slope.							
34.30	Gravelled road, 15 lks. wide, bears N. 30° E. and S. 30° W.							
37.65	Ridge, bears N. 30° E. and S. 30° W.; desc. over NW. slope.							
43.70	Gravelled road, 15 lks. wide, bears E. and W.							
62.00	Creek, 1 lk. wide, course N. 80° W.; asc. over SW. slope.							
63.25	Intersect the S. bdy. of T. 30 S., R. 4 W.							
	True point for the closing cor. of secs. 1 and 2.							
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.							
	<table style="margin: auto; border-collapse: collapse;"> <tr><td style="padding: 0 10px;">T 30 S R 4 W</td></tr> <tr><td style="padding: 0 10px; text-align: center;">S 35</td></tr> <tr><td style="padding: 0 10px; text-align: center;">-----</td></tr> <tr><td style="padding: 0 10px; text-align: center;">S 2   S 1</td></tr> <tr><td style="padding: 0 10px; text-align: center;">C C</td></tr> <tr><td style="padding: 0 10px;">T 31 S R 4 W</td></tr> <tr><td style="padding: 0 10px;">1985</td></tr> </table>	T 30 S R 4 W	S 35	-----	S 2   S 1	C C	T 31 S R 4 W	1985
T 30 S R 4 W								
S 35								
-----								
S 2   S 1								
C C								
T 31 S R 4 W								
1985								
	from which							
	A fir, 8 ins. diam., bears S. 71° E., 7 lks. dist., mkd. T31S R4W S1 CC BT.							
	A fir, 6 ins. diam., bears S. 72°W., 35 lks. dist., mkd. T31S R4W S2 CC BT.							
	Deposit white "DEEP-1" magnetic marker at base of stainless steel post.							
	From this point, the original closing cor. of secs. 1 and 2, bears N. 0° 35' E., 0.10 chs. dist., perpetuated and recorded by John H. Markham, Jr., Registered Engineer No. 2880, in 1959, monumented with the original corner stone, 13 x 10 x 5, lying loose on the ground, mkd. CC on face, (alongside of which is an iron pipe, 1 in. diam., firmly set, projecting 4 ins. above ground,) from which the original bearing trees:							
	A fir, 26 ins. diam., bears N. 71½° E., 48 lks. dist., with healed blaze. (Record, N. 69¼° E., 52 lks.)							
	A fir, 40 ins. diam., bears S. 68° W., 15 lks. dist., with healed blaze. (Record, S. 72½° W., 16 lks.)							
	and bearing trees mkd. by Markham							
	A madrone, 14 ins. diam., bears N. 55° E., 46 lks. dist., with scribe marks BT S35 T30S R4W visible on bark blaze.							