

County Surveyor's Record, Douglas County, Oregon

18145 Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 31 S., R. 4 W., Willamette, Meridian, Oregon

CHAINS

A madrone, 12 ins. diam., bears S. $89\frac{1}{2}^{\circ}$ E., 29 lks. dist., with scribe marks BT S1 T31S R4W visible on bark blaze.

A madrone, 9 ins. diam., bears N. $69\frac{1}{2}^{\circ}$ W., 23 lks. dist., with fragmentary scribe marks visible on partially healed double blaze.

From this same point, the cor. of secs. 35 and 36 only, T. 30 S., R. 4 W., bears N. $89^{\circ} 31'$ E., 5.295 chs. dist., hereinbefore described.

Land, mountainous.

Soil, rocky clay.

Timber, fir, cedar, alder, chinquapin, maple, yew hemlock, pine, madrone, and dogwood; undergrowth, poison oak, salal, Oregon grape, blackberry, ferns, arrowwood, hazel, vine maple, manzanita, ceanothus, and young timber.

The point for the $\frac{1}{4}$ sec. cor. of sec. 1 only is at midpoint longitudinally, on the N. bdy. of sec. 1.

Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \text{T 30 S R 3 W} \\ \hline \frac{1}{4} \text{ S 1} \\ \text{T 31 S R 4 W} \\ 1985 \end{array}$$

from which

A madrone, 15 ins. diam., bears S. 3° E., 9 lks. dist., mkd. $\frac{1}{4}$ S1 BT on bark.

A fir, 40 ins. diam., bears S. 23° W., 42 lks. dist., mkd. $\frac{1}{4}$ S1 BT.

From this point, the cor. of Tps., 30 S., Rs. 3 and 4 W., bears S. $89^{\circ} 29' W.$, 2.64 chs. dist., hereinbefore described.

From the cor. of secs. 14, 15, 22, and 23, perpetuated and recorded by John H. Markham, Jr., Registered Engineer No. 2880, in 1959, monumented with an iron pipe, 2 ins. diam., firmly set, projecting 13 ins. above ground, from which the original bearing trees:

A fir, 30 ins. diam., bears S. 32° E., 27 lks. dist., with healed blaze.

A fir, 44 ins. diam., bears N. $49\frac{1}{4}^{\circ}$ W., 32 lks. dist., with healed blaze.

and bearing trees mkd. by Markham

A cedar, 15 ins. diam., bears S. 11° E., $65\frac{1}{2}$ lks. dist., with healed blaze.

A maple, 13 ins. diam., bears S. 10° W., 34 lks. dist., with healed blaze.

A hemlock, 13 ins. diam., bears S. 35° W., 34 lks. dist., with healed blaze.