

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 31 S., R 4 W., Willamette Meridian, Oregon 18146

**CHAINS**

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam.,  
24 ins. in the ground, with brass cap mkd.

T 31 S R 4 W	
S 15	S 14
S 22	S 23
1985	

Deposit iron pipe alongside and a white "DEEP-1"  
magnetic marker at base of stainless steel post.

S. 88° 46' W., bet. secs. 15 and 22.

Over broken NW. slope, through moderate timber and dense  
undergrowth.

2.10

Creek, 5 lks. wide, course N 20° W,; asc. NE. slope.

40.62

Point for the ¼ sec. cor. of secs. 15 and 22, at propor-  
tionate distance; there is no remaining evidence of the  
original corner.

Set a stainless steel post, 28 ins. long, 2½ ins. diam.,  
24 ins. in the ground, with brass cap mkd.

T 31 S R 4 W	
¼ S 15	S 22
1985	

from which

A fir, 13 ins. diam., bears N. 84° E., 43  
lks. dist., mkd. ¼ S15 BT.

A fir, 8 ins. diam., bears S. 64½° W., 13  
lks. dist., mkd. ¼ S22 BT.

Deposit a white "DEEP-1" magnetic marker at  
base of stainless steel post.

The corner is located on NE. slope, 100 lks. N. of a  
gravel road, 25 lks. wide, bears N. 65° W. and S. 65° E.

Continue over broken N. slope.

45.20

Gravelled road, 20 lks. wide, bears S. 80° E. and  
S. 80° W.

76.45

Leave timber, edge bears N. 25° E. and S. 35° W.; enter  
logged area.

81.24

The cor. of secs. 15, 16, 21, and 22, perpetuated and  
recorded by John M. Powell, Deputy County Surveyor, in  
1966, monumented with an iron post, 1½ ins. diam.,  
firmly set, projecting 12 ins. above ground, with brass  
cap mkd.

COUNTY SURVEYOR	
OFFICE	
T31S R4W	
S 16	S 15
S 21	S 22
1966	