

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 31 S., R. 4 W., Willamette Meridian, Oregon

18148

CHAINS

- 55.45 Top of ascent; desc. over NE. slope.
- 58.65 Ravine, drains S. 80° E.; asc. SE. slope.
- 70.95 Top of ascent, desc. NE. slope.
- 80.74 The cor. of secs. 9, 10, 15, and 16, perpetuated and recorded by John M. Powell, Deputy County Surveyor, in 1966, monumented with an iron post, 1½ ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

COUNTY SURVEYOR
OFFICE
T 31 S R 4 W
S 9 | S 10
S 16 | S 15
1966

from which the original bearing trees

A fir, 23 ins. diam., bears N. 66° E.,
35 lks. dist., with healed blaze.

A fir, 50 ins. diam., bears S. 57° W.,
17 lks. dist., with healed blaze.

and bearing trees mkd. by Powell

A cedar, 23 ins. diam., bears S. 49° E.,
24 lks. dist., with healed blaze.

and a new bearing tree

A fir, 7 ins. diam., bears N. 14½° W.,
44 lks. dist., mkd. T31S R4W S9 BT.

From the ¼ sec. cor. of secs. 8 and 9, perpetuated and recorded by John H. Markham, Jr., Registered Engineer No. 2880, in 1951, monumented with the original corner tree, a Douglas fir, 28 ins. diam., with healed blaze on W. side, from which the remains of the original bearing trees:

A fir, 38 ins. diam., bears S. 42 3/4° E., 23
lks. dist., with healed blaze.

A fir, stump, 34 ins. diam., bears N. 53½° W., 15
lks. dist., with healed blaze.

and bearing trees of no known record

A fir, 18 ins. diam., bears S. 71° W., 20
lks. dist., with healed blaze.

A fir, 16 ins. diam., bears N. 10° W., 6
lks. dist., with healed blaze.

and a reference point set by the County Surveyors Office, in 1966.

An iron post, 1 in. diam., firmly set, projecting 14 ins. above ground, bears West, 3 lks. dist., with brass cap mkd. COUNTY SURVEYORS OFFICE T31S R4W ¼ S8 S9 1966.