

# County Surveyor's Record, Douglas County, Oregon

**18149** Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 31 S., R. 4 W., Willamette Meridian, Oregon

**CHAINS**

N. 1° 07' E., bet. secs. 8 and 9.

Descend over NW. slope, through moderate timber and dense undergrowth.

4.85 Creek, 5 lks. wide, course N. 80° W.; asc. SW slope.

17.10 Dirt road, 15 lks. wide, bears N. 60° W. and S. 60° E.; also spur, slopes NW.; desc. N. slope.

27.65 Gravelled road, 20 lks. wide, bears N. 30° W. and S. 55° E.

38.25 Creek, 6 lks. wide, course N. 70° W.; asc. SE. slope.

39.52 Point for the cor. of secs. 4, 5, 8, and 9, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 31 S R 4 W			
S 5		S 4	
S 8		S 9	
1985			

from which

A fir, 8 ins. diam., bears N. 33° E., 35 lks. dist., mkd. T31S R4W S4 BT.

A fir, 8 ins. diam., bears S. 64° E., 29 lks. dist. mkd. T31S R4W S9 BT.

A fir, 12 ins. diam., bears S. 77½° W., 30½ lks. dist., mkd. T31S R4W S8 BT.

A fir, 29 ins. diam., bears N. 82½° W., 76½ lks. dist., mkd. T31S R4W S5 BT.

Deposit white "DEEP-1" magnetic marker at base of stainless steel post.

From the cor. of secs. 3, 4, 9, and 10, perpetuated and recorded by M. Lenora Ladig, County Surveyors Office, in 1976, monumented with a 1½ in diam., iron post, firmly set, projecting 5 ins. above ground (alongside of which is a 1 in. diam. galvanized pipe, firmly set, projecting 3 ins. above ground,) with brass cap mkd.

T 31 S R 4 W			
S 4		S 3	
S 9		S 10	
1976			

from which the remains of the original bearing trees

A fir, 42 ins. diam., bears N. 15° E., 51 lks. dist., with healed blaze.

A fir, 30 ins. diam., bears S. 20° W., 82 lks. dist., with healed blaze.

A fir, 24 ins. diam., bears N. 81 3/4° W., 85 lks. dist., with healed blaze. (Record, 91 lks.)