

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of the Subdivisional Lines
T. 31 S., R. 4 W., Willamette Meridian, Oregon 18150

CHAINS

and a bearing tree of no known record.

A madrone, 12 ins. diam., bears N. 65½° E., 43 lks. dist., mkd. S3 T31S R4W.

N. 89° 42' W., bet. secs. 4 and 9.

Ascend over SE. slope, through logged area.

8.85 Top of ascent; desc. over broken SW. slope.

15.80 Enter timber, edge bears S. and W.

18.70 Ravine, drains S. 24° E.; asc. over steep NE. slope, along E. and W. timber line, young reproduction to N., old growth to S.

34.20 Spring branch, dry, 5 lks. wide, course S. 50° E.

37.66 Point for the ¼ sec. cor. of secs. 4 and 9, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 31 S R 4 W
 S 4
 ¼
 S 9
 1985

from which

A fir, 14 ins. diam., bears S. 44° E., 46 lks. dist., mkd. ¼ S9 BT.

A fir, 10 ins. diam., bears N. 20 ¾° W., 32 lks. dist., mkd. ¼ S4 BT.

Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.

From this point, a point established and recorded by John H. Markham, Jr., Registered Engineer No. 2880, in 1951, subsequently perpetuated and recorded by M. Lenora Ladig, County Surveyors Office, in 1976, bears N. 35° 19' E., 0.303 chs. dist., monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground (alongside are two iron pipes, 1 in. diam., both firmly set,) with brass cap mkd. T31S R4W ¼ S4 S9 1976, from which the remains of the bearing trees mkd. by Markham:

A fir snag, 42 ins. diam., bears N. 19° E., 16 lks. dist., with fragmentary scribe marks ¼ S4 T31S R4W visible.

A fir snag, 42 ins. diam., bears S. 61° E., 44 lks. dist., no marks visible.

and the remains of the bearing trees mkd. by the County Surveyors Office.

A fir snag, 11 ins. diam., bears S. 40° E., 35 lks. dist., with pitched over blaze.