

County Surveyor's Record, Douglas County, Oregon

18153 Dependent Resurvey, Portion of the Subdivisional Lines,
T. 31 S., R 4 W., Willamette Meridian, Oregon

CHAINS

Set a stainless steel post, 28 ins. long, 2½ ins. diam.,
24 ins. in the ground, with brass cap mkd.

T 30 S R 4 W
 $\frac{S 32}{S 5 \quad | \quad S 4}$
 T 31 S
 C C
 1985

from which

A Douglas fir, 14 ins. diam., bears S. 27½° E.,
47 lks. dist., mkd. T31S R4W S4 CC BT.

A Douglas fir, 16 ins. diam., bears S. 60° W.,
17½ lks. dist., mkd. T31S R4W S5 CC BT.

From this point, the cor. of secs. 4, 5, 32, and 33, on
the N. bdy. of the Tp., now an angle point, bears
N. 89° 06' E., 9.53 chs. dist., hereinbefore described.

From the cor. of secs. 29, 30, 31, and 32, perpetuated
and recorded by John M. Powell, Deputy County Surveyor,
in 1966, monumented with an iron post, 1½ ins. diam.,
firmly set, projecting 12 ins. above ground, in a mound
of stone, 3 ft. base, 1 ft. high, with brass cap mkd.

COUNTY SURVEYORS OFFICE
 T 31 S R 4 W
 $\frac{S 30 \quad | \quad S 29}{S 31 \quad | \quad S 32}$
 1966

from which the original bearing trees

A fir, 32 ins. diam., bears S. 12 ¾° W., 14
lks. dist., with healed blaze.

A fir, 33 ins. diam., bears N. 74° W., 26½
lks. dist., with healed blaze.

and bearing trees mkd. by Powell.

A fir, 41 ins. diam., bears N. 86 ¾° E., 11
lks. dist., with healed double blaze.

A fir, 40 ins. diam., bears S. 47½° E., 42
lks. dist., with healed double blaze.

N. 89° 49' W., bet. secs. 30 and 31.

Descend over broken SW. slope, through heavy timber and
dense undergrowth.

19.935

Point for the E 1/16 sec. cor. of secs. 30 and 31.

Set an iron post, 30 ins. long, 2½ ins. diam., with
magnetic breakaway base, 24 ins. in the ground, with
brass cap mkd.

E 1/16 $\frac{S 30}{S 31}$
 1984