

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of the Subdivisional Line
T. 31 S., R 4 W., Willamette Meridian, Oregon 18154

CHAINS	
	<p>From which</p> <p style="margin-left: 40px;">A fir, 5 ins. diam., bears N. 29½° E., 20 lks. dist., mkd. X BT.</p> <p style="margin-left: 40px;">A fir, 10 ins. diam., bears S. 62 3/4° E., 6 lks. dist., mkd. E 1/16 S31 BT.</p> <p>Descend over broken SW. slope.</p>
24.70	<p>Russell Creek, 3 lks. wide, course S. 30° E.; asc. over NE. slope.</p>
31.35	<p>Three wire power transmission line, bears N. 25° W. and S 25° E.</p>
39.87	<p>The ¼ sec. cor. of secs. 30 and 31, perpetuated and recorded by John M. Powell, Deputy County Surveyor, in 1966, monumented with an iron post, 1½ ins. diam., firmly set, projecting 18 ins. above ground, with brass cap mkd.</p>
<p>COUNTY SURVEYORS OFFICE T 31 S R 4 W ¼ $\frac{S\ 30}{S\ 31}$ 1966</p>	
	<p>from which the remains of the original bearing trees</p> <p style="margin-left: 40px;">A fir, 26 ins. diam., bears N. 24° E., 33 lks. dist., with scribe marks ¼ S visible on bark blaze.</p> <p style="margin-left: 40px;">A fir snag, 12 ins. diam., bears S. 45½° W., 12 lks. dist., with healed blaze.</p> <p>and a bearing tree mkd. by Powell</p> <p style="margin-left: 40px;">A fir, 28 ins. diam., bears S. 31½° E., 58 lks. dist., with healed double blaze.</p>
	<p style="text-align: center;">S 89° 54' W., beginning new measurement.</p> <p>Ascend over NE. slope.</p>
17.95	<p>Spur, slopes S. 10° E.; desc. over SW slope.</p>
20.265	<p>Point for the W 1/16 sec. cor. of secs. 30 and 31.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">W 1/16 $\frac{S\ 30}{S\ 31}$ 1984</p>
	<p>From which</p> <p style="margin-left: 40px;">A fir, 10 ins. diam., bears S. 38° W., 10½ lks. dist., mkd. W 1/16 S31 BT.</p> <p style="margin-left: 40px;">A fir, 9 ins. diam., bears N. 7½° W., 24 lks. dist., mkd. W 1/16 S30 BT.</p>