

County Surveyor's Record, Douglas County, Oregon

18155 Dependent Resurvey, Portion of the Subdivisional Lines,
T. 31 S., R. 4 W., Willamette Meridian, Oregon

CHAINS																
39.20	<p>Descend over SW. slope.</p> <p>Intersect the E. bdy. of T. 31 S., R. 5 W.</p> <p>True point for the closing cor. of secs. 30 and 31.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td></td><td style="text-align: center;">T 31 S</td><td></td></tr> <tr><td style="text-align: center;">R 5 W</td><td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;"> </td><td style="text-align: center;">R 4 W</td></tr> <tr><td></td><td style="text-align: center;">S 30</td><td></td></tr> <tr><td style="text-align: center;">S 25</td><td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;"> </td><td style="text-align: center;">S 31</td></tr> <tr><td></td><td style="text-align: center;">1985</td><td style="text-align: right;">CC</td></tr> </table> </div> <p>from which</p> <p style="margin-left: 40px;">A fir, 7 ins. diam., bears N. 30° E., 21½ lks. dist., mkd. T31S R4W S30 CC BT.</p> <p style="margin-left: 40px;">A fir, 10 ins. diam., bears S. 46½° E., 19 lks. dist., mkd. T31S R4W S31 CC BT.</p> <p>The corner is located on steep S. slope.</p> <p>From this point, the original closing cor. of secs. 30 and 31, bears S. 89° 54' W., 0.065 chs. dist., perpetuated and recorded by John M. Powell, Deputy County Surveyor, in 1966, monumented with an iron post, 1½ ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. COUNTY SURVEYORS OFFICE T31S R4W R5W S30 S31 S25 1966, from which the remains of an original bearing tree:</p> <p style="margin-left: 40px;">A decayed fir stump, 30 ins. diam., bears S. 39½° W., 29 lks. dist., rescribed by Powell with scribe marks BT visible.</p> <p>and bearing trees mkd. by Powell</p> <p style="margin-left: 40px;">A fir, 14 ins. diam., bears N. 20° E., 26 lks. dist., with healed blaze.</p> <p style="margin-left: 40px;">A Double fir, 9 ins. diam., bears N. 80° E., 29 lks. dist., with healed double blaze.</p> <p>From this same point, the cor. of secs. 25 and 36, T. 31 S., R. 5 W., bears S. 0° 09' W., 3.61 chs. dist., hereinbefore described.</p> <p>Land, mountainous. Soil, rocky clay. Timber, fir, cedar, madrone, pine, hemlock, yew, alder, chinquapin, and oak; undergrowth, poison oak, salal, Oregon grape, arrowwood, blackberry, manzanita, ceanothus, huckleberry, ferns, and young timber.</p>		T 31 S		R 5 W		R 4 W		S 30		S 25		S 31		1985	CC
	T 31 S															
R 5 W		R 4 W														
	S 30															
S 25		S 31														
	1985	CC														
14.05	<p>From the cor. of secs. 29, 30, 31, and 32.</p> <p>North, bet. secs. 29 and 30.</p> <p>Ascend over SW. slope, through heavy timber and dense undergrowth.</p> <p>Gravelled road, 20 lks. wide, bears N. 20° W., and S. 20° E.</p>															