

# County Surveyor's Record, Douglas County, Oregon

18157 Dependent Resurvey, Portion of the Subdivisional Lines,  
T. 31 S., R. 4 W., Willamette Meridian, Oregon

CHAINS																	
40.645	<p>The cor. of secs. 19, 20, 29, and 30, perpetuated and recorded by John H. Markhem, Jr., Registered Engineer No. 2880, in 1959, monumented with the original stone, 18 x 10 x 6 ins., firmly set, projecting 10 ins. above ground, with 2 notches on S. edge, ( alongside of which is an iron pipe, 1 in. diam., firmly set, projecting 10 ins. above ground,) from which the remains of the original bearing trees:</p> <p style="margin-left: 40px;">A decayed fir stump, 40 ins. diam., bears N. 14¼° E., 425 lks. dist., no marks visible.</p> <p style="margin-left: 40px;">A fir 45 ins. diam., bears S. 3½° E., 72 lks. dist., with healed blaze. (Record, 75 lks.)</p> <p>and bearing trees mkd. by Markham</p> <p style="margin-left: 40px;">A fir, 13 ins. diam., bears N. 80° E., 13 lks. dist., with healed double blaze.</p> <p style="margin-left: 40px;">A fir, 15 ins. diam., bears S. 3° W., 11 lks. dist., with healed double blaze.</p> <p style="margin-left: 40px;">A fir, 11 ins. diam., bears S. 86° W., 8 lks. dist., with healed double blaze.</p> <p style="margin-left: 40px;">A fir, 6 ins. diam., bears N. 22° W., 3 lks. dist., with fragmentary scribe marks visible on partially healed double blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="4">T 31 S R 4 W</td> </tr> <tr> <td style="border-right: 1px solid black; border-bottom: 1px solid black; padding: 2px 5px;">S 19</td> <td style="border-bottom: 1px solid black; padding: 2px 5px;">S 20</td> <td colspan="2"></td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S 30</td> <td style="padding: 2px 5px;">S 29</td> <td colspan="2"></td> </tr> <tr> <td colspan="4" style="text-align: center; padding: 2px 5px;">1985</td> </tr> </table> </div> <p>from which a new bearing tree</p> <p style="margin-left: 40px;">A fir, 20 ins. diam., bears N. 31° W., 28 lks. dist., mkd. T31S R4W S19 BT.</p> <p style="margin-left: 40px;">Deposit original stone and iron pipe alongside, and white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Land, mountainous. Soil, rocky clay. Timber, fir, cedar, hemlock, pine, yew, madrone, oak, chinquapin, and alder; undergrowth, poison oak, ferns, salal, arrowwood, manzanita, huckleberry, hazel, vine, maple, and young timber.</p>	T 31 S R 4 W				S 19	S 20			S 30	S 29			1985			
T 31 S R 4 W																	
S 19	S 20																
S 30	S 29																
1985																	
16.56	<p>S. 89° 21' W., bet. secs. 19 and 30.</p> <p>Descend over NW. slope, through heavy timber and dense undergrowth.</p> <p>An original line tree, a fir, 48 ins. diam., with 2 hack marks on E. and W. faces. This now becomes an angle point.</p>																