

County Surveyor's Record, Douglas County, Oregon

18161 Dependent Resurvey, Portion of the Subdivisional Lines,
T. 31 S., R. 4 W., Willamette Meridian, Oregon

CHAINS																
	<p>from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A fir, 44 ins. diam., bears S. 56½° W., 36 3/4 lks. dist., no marks visible on opened blaze.</p> <p style="padding-left: 40px;">A down, decayed madrone, size indeterminate, bears N. 64½° W., 22½ lks. dist., no marks visible on rotted face.</p> <p>and the remains of the bearing trees mkd. by Powell</p> <p style="padding-left: 40px;">A cedar, 10 ins. diam., bears N. 51° E., 9½ lks. dist., with scribe marks ¼ S5 visible on partially healed blaze.</p> <p style="padding-left: 40px;">A down cedar, 18 ins. diam., bears N. 53½° E., 17 lks. dist., with scribe marks ¼ S8 CS visible on open blaze.</p>															
	<p>Subdivision of Section 30, T. 31 S., R. 4 W., Willamette Meridian, Oregon</p>															
	<p>From the ¼ sec. cor. of secs. 30 and 31.</p> <p>N.0° 07' E., on the N. and S. center line of sec. 30.</p> <p>Ascend over SE. slope, through heavy timber and dense undergrowth.</p>															
14.80	Dirt road, 15 lks. wide, bears N. 65° E. and S. 65° W.															
18.30	Ridge, bears N. 75° E. and S. 75° W.; desc. over broken NE. slope.															
20.09	<p>Point for the center S 1/16 sec. cor. of sec. 30.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border: none;"> <tr><td></td><td style="text-align: center;">C</td><td></td></tr> <tr><td></td><td style="text-align: center;">S 1/16</td><td style="text-align: center;"> </td><td style="text-align: center;">S 30</td></tr> <tr><td></td><td></td><td style="text-align: center;">C</td><td></td></tr> <tr><td></td><td></td><td style="text-align: center;">1985</td><td></td></tr> </table> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears S. 75° E., 33 lks. dist., mkd. CS 1/16 S30 BT.</p> <p style="padding-left: 40px;">A fir, 10 ins. dima., bears N. 52° W., 30 lks. dist., mkd. CS 1/16 S30 BT.</p> <p style="padding-left: 40px;">Deposit white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Descend over broken NE. slope.</p>		C			S 1/16		S 30			C				1985	
	C															
	S 1/16		S 30													
		C														
		1985														
22.05	Dirt road, 15 lks. wide, bears N. 70° W. and S. 70° E.															
40.18	Point for the center ¼ sec. cor. of sec. 30, at intersection with the E. and W. center line.															