

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 30
T. 31 S., R. 4 W., Willamette Meridian, Oregon

18162

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 31 S R 4 W C ¼ S 30 1985</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears S. 44° W., 28 lks. dist., mkd. C¼ S30 BT.</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears N. 20¼° W., 28 lks. dist., mkd. C¼ S30 BT.</p> <p style="padding-left: 40px;">Deposit white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Descend over broken NE. slope.</p>
57.05	Packard Creek, 5 lks. wide, course N. 50° W.; asc. over SW slope.
80.50	The ¼ sec. cor. of secs. 19 and 30.
	<p>From the ¼ sec. cor. of secs. 29 and 30.</p> <p>S 89° 41' W., on the E. and W. center line of sec. 30.</p> <p>Descend over broken SW. slope, through heavy timber and dense undergrowth.</p>
13.10	Packard Creek, 4 lks. wide, course N. 60° W.; asc. over broken NE. slope.
19.89	<p>Point for the center E 1/16 sec. cor. of sec. 30.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">C $\frac{E\ 1/16}{S\ 30}$ C 1985</p> <p>from which</p> <p style="padding-left: 40px;">A hemlock, 10 ins. diam., bears N. 77½° E., 22 lks. dist., mkd. CE 1/16 S30 BT.</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears N. 84¼° W., 22 lks. dist., mkd. CE 1/16 S30 BT.</p> <p style="padding-left: 40px;">Deposit white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Ascend over broken NE. slope.</p>
39.40	Creek, 3 lks. wide, course N. 10° E.; asc. over broken NE. slope.
39.78	<p>The center ¼ sec. cor. of sec. 30.</p> <p>Ascend over broken NE. slope.</p>