

# County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 30,  
T 31 S., R 4 W., Willamette Meridian, Oregon

18164

CHAINS	
	SE 1/16 S 30 1985
	from which
	A cedar, 10 ins. diam., bears S. 18° W., 13 lks. dist., mkd. SE 1/16 S30 BT.
	A fir, 6 ins. diam., bears N. 70½° W., 23 lks. dist., mkd. SE 1/16 S30 BT.
	Deposit white "DEEP-1" magnetic marker at base of stainless steel post.
	Ascend over SW. slope.
25.45	Dirt road, 15 lks. wide, bears N. 50° E. and S. 60° W.
26.30	Ridge, bears N. 75° E. and S. 75° W.; desc. over NE. slope.
40.35	The center E 1/16 sec. cor. of sec. 30.
	from the S 1/16 sec. cor. of secs. 29 and 30.
	S. 89° 55' W., on the E. and W. center line of the SE ¼ of sec. 30.
	Descend over SW. slope, through heavy timber and dense undergrowth.
1.40	Gravelled road, 15 lks. wide, bears N. 40° W. and S 20° E., in a curve.
19.92	The SE 1/16 sec. cor. of sec. 30.
	Descend over SW. slope.
35.35	Dirt road, 15 lks. wide, bears N. 50° E. and S. 50° W.
36.05	Ridge, bears N. 60° E. and S. 60° W., along broken N. slope.
39.83	The center S 1/16 sec. cor. of sec. 30.
	From the W 1/16 sec. cor. of secs. 30 and 31.
	N. 0° 17' E., on the N. and S. center line of the SW¼ of sec. 30.
	Ascend over SW. slope, through heavy timber and dense undergrowth.
2.90	Ridge, bears N. 85° W. and S. 85° E.; desc. over NE. slope.
4.85	Dirt road, 15 lks. wide, bears N. 85° W. and S. 85° E.
17.10	Creek, 3 lks. wide, course NW.; continue to desc. over NE. slope.
20.055	Point for the SW 1/16 sec. cor. of sec. 30, at inter- section with the E. and W. center line of the SW¼.