

County Surveyor's Record, Douglas County, Oregon

18169 Dependent Resurvey, Portion of the Subdivisional Lines,
T. 25 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

(Restoring the survey by Dennis Hathorn, in 1857,
and the resurvey by Irving Zirpel, Jr., in 1958)

Beginning at the cor. of secs. 9, 10, 15, and 16,
monumented with an iron post, 2½ ins. diam., firmly set,
projecting 4 ins. above ground, with brass cap mkd.

T 25 S R 7 W.	
S 9	S 10
S 16	S 15
1958	

from which the remains of the original bearing trees

A root hole, bears S. 70° W., 42 lks. dist., with an
uprooted fir stump alongside, 53 ins. diam., no
marks visible.

A fir snag, 49 ins. diam., bears N. 2° W., 60 lks.
dist., with scribe marks S9 BT visible on bark
blaze.

and the remains of a local bearing tree recorded by
Zirpel

A fir snag, 40 ins. diam., bears N. 71¼° E.,
51 ½ lks. dist., with illegible scribe marks
visible on bark blaze.

and the remains of a bearing tree mkd. by Zirpel

A fir snag, 12 ins. diam., bears S. 8¼° E., 114 lks.
dist., no marks visible on decayed blaze.

and the remains of bearing trees mkd. by Roseberry

A fir snag, 23 ins. diam., bears S. 70¼° E., 113
lks. dist., with scribe marks T25S R7W S15 BT
visible an open blaze.

A cedar, 25 ins. diam., bears S. 60½° W., 73 lks.
dist., with healed blaze.

and new bearing trees

A fir, 8 ins. diam., bears N. 19¼° E., 19 lks.
dist., mkd. T25S R7W S10 BT.

A fir, 7 ins. diam., bears S. 9° E., 115 lks.
dist., mkd. T25S R7W S15 BT.

A fir, 5 ins. diam., bears N. 30½° W., 26 lks.
dist., mkd. T25S R7W S9 BT.

N. 0° 38' W., bet. secs. 9 and 10, marking and blazing
the true line.

Descend over N. slope, through heavy timber and dense
undergrowth.

1.245

The meander cor. of secs. 9 and 10, on the left bank of
the Umpqua River, monumented with an iron post, 2½ ins.
diam., firmly set, with top 8 ins. below surface of
ground, with brass cap mkd.