

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of the Subdivisional Lines, **18170**  
T. 25 S., R 7 W., Willamette Meridian, Oregon

CHAINS	
	<div style="margin-bottom: 10px;"> <math display="block">\begin{array}{c} \text{MC} \\ \hline \text{S } 9 \mid \text{S } 10 \\ \text{T } 25 \text{ S } \text{ R } 7 \text{ W} \\ 1958 \end{array}</math> </div> <p>from which bearing trees mkd. by Zirpel</p> <p style="margin-left: 40px;">A fir, 25 ins. diam., bears S. <math>41\frac{1}{2}^\circ</math> E., 68 lks. dist., with healed blaze.</p> <p style="margin-left: 40px;">A fir, 25 ins. diam., bears S. <math>84^\circ</math> W., 106 lks. dist., with healed blaze. (Record, 108 lks.)</p>
	<p>From the cor. of secs. 9, 10, 15, and 16.</p> <p>N. <math>88^\circ 59'</math> W., bet. secs. 9 and 16.</p> <p>Ascend gentle NE. slope, through heavy timber and dense undergrowth.</p>
16.15	Top of ascent, slopes N.; continue over broken NE. slope.
30.50	Begin descent over gentle NW. slope.
35.20	Creek, 5 lks. wide, course N. $12^\circ$ W.; asc. NE. slope.
42.77	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 9 and 16, perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1959, monumented with an iron post, <math>1\frac{1}{4}</math> ins. diam., firmly set flush with ground, with brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS OFFICE</p> $\begin{array}{c} \frac{1}{4} \text{ S } 9 \\ \hline \text{S } 16 \\ \text{T } 25 \text{ S } \text{ R } 7 \text{ W} \\ 1959 \end{array}$ <p>from which the remains of an original bearing tree</p> <p style="margin-left: 40px;">A decayed fir stump, 20 ins. diam., bears S. <math>25\frac{1}{2}^\circ</math> W., <math>35\frac{1}{2}</math> lks. dist., with scribe marks BT visible on opened blaze. (Record, S. <math>13^\circ</math> E., 34 lks.)</p> <p>and a bearing tree mkd. by Claude Kerr, Registered Professional Engineer, in 1953</p> <p style="margin-left: 40px;">A fir, 28 ins. diam., bears N. <math>64\frac{1}{2}^\circ</math> W., 21 lks. dist., no marks visible on opened blaze.</p> <p>and a bearing tree mkd. by Byron</p> <p style="margin-left: 40px;">A fir, 29 ins. diam., bears S. <math>83^\circ</math> E., 69 lks. dist., with healed blaze.</p> <p>From this point, Douglas County Surveyors Office Horizontal Control Station U-10, at latitude <math>43^\circ 24' 24.85''</math> N. and longitude <math>123^\circ 32' 08.36''</math> W., bears N. <math>8^\circ 51'</math> W., 18.90 chs. dist., monumented with a brass tablet, firmly set in concrete, flush with ground, with tablet mkd. U-10 1972.</p>
	<p style="text-align: center;">N. <math>89^\circ 21'</math> W., beginning new measurement.</p>