

# County Surveyor's Record, Douglas County, Oregon

**18173** Dependent Resurvey, Portion the Subdivisional Lines,  
T. 25 S., R. 7 W., Willamette Meridian, Oregon

**CHAINS**

An oak, 37 ins. diam., bears S. 10° E., 290 lks.  
dist., no marks visible on open burned blaze.

and bearing trees mkd. by the County Surveyors Office,  
in 1923

An oak, 20 ins. diam., bears N. 46½° E., 167 lks.  
dist., no marks visible on opened blaze.

An oak, 29 ins. diam., bears S. 64¼° W., 124 lks.  
dist., with healed blaze.

and bearing trees mkd. by Godfrey

A fir, 28 ins. diam., bears S. 36° E., 20½ lks.  
dist., with healed blaze.

A fir, 25 ins. diam., bears N. 82° W., 30 lks.  
dist., with healed blaze.

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam.  
24 ins. in the ground, with brass cap mkd.

T 25 S. R 7 W.  
          ½  
          S 8 | S 9  
          1985

Deposit a white "DEEP-1" magnetic marker at base  
of stainless steel post.

Retracement of the Meanders of the Left Bank  
of the Umpqua River in Section 9.  
T. 25 S., R 7 W., Willamette Meridian, Oregon.

From the meander cor. of secs. 9 and 10, on the left  
bank of the Umpqua River.

Thense downstream with the adjusted record meanders of  
the left bank of the Umpqua River in sec. 9.

N. 82° 25' W., 38.65 chs.

N. 74° 34' W., 43.88 chs. At 4.37 chs. on this course,  
point for the special meander  
cor. on the N. and S. center  
line of sec. 9, hereinafter  
described.

At end of course, the true  
point for the meander cor. of  
secs. 8 and 9, on the left  
bank of the Umpqua River.

Subdivision of Section 9,  
T. 25 S., R 7 W., Willamette Meridian, Oregon

From the ¼ sec. cor. of secs. 9 and 16.

N. 1° 51' E., on the N. and S. center line of sec. 9.