

# County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 9,  
T. 25 S., R 7 W., Willamette Meridian, Oregon

18174


**CHAINS**

Descend over gentle NW. slope, through heavy timber and moderate undergrowth.

1.20 Gravelled road, 20 lks. wide, bears S. 80° E. and W.

6.76 Intersect the adjusted record meanders on the left bank of the Umpqua River, point for the special meander cor. on the N. and S. center line of sec. 9.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.



from which

A fir, 11 ins. diam., bears S. 29½° E., 27 lks. dist., mkd. S 9 SMC BT.

A cedar, 10 ins. diam., bears S. 57° W., 13½ lks. dist., mkd. S9 SMC BT.

Deposit a white "DEEP-1" marker at base of iron post.


8.40 Left bank of the Umpqua River, bears N. 80° W. and S 80° E., course N. 80° W.; thence across the river.

13.70 Right bank of the Umpqua River, bears N. 80° W., and S. 80° E.; asc. over gentle S. slope, through light timber and moderate undergrowth.

18.25 Tyee Road, 35 lks. wide, bears E. and W.

40.18 Point for the center ¼ sec. cor. of sec. 9, at intersection with the E. and W. center line.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.



from which

A fir, 10 ins. diam., bears N. 78½° E., 13 lks. dist., mkd. C ¼ S9 BT.

A white fir, 14 ins. diam., bears S. 54½° E., 20 lks. dist., mkd. C ¼ S9 BT.

Deposit a white "DEEP-1" magnetic marker at base of iron post.

Corner is located N. 56½° W., 9 lks. dist. from a fence corner, fence lines bear N., E., and S.

Continue over broken SW slope.

80.13 The ¼ sec. cor. of secs. 4 and 9, monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

*FD. OK.  
DCSO  
12/1/89  
C.S. 64/3*